

Principal dimensions				Basic load ratings		Basic load ratings		Limiting Speed		Designation	Distance of action point	Installation dimensions			Weight
外形尺寸				额定载荷		额定载荷		极限转速		轴承代号	作用点距离	安装尺寸 (mm)			重量
d	D	B	r	Cr	Cor	Cr	Cor	(rpm)			a ₀	d _a	Da	r _a	(kg)
			min(最小)	(N)	{kgf}	脂润滑	油润滑	(mm)	min(最小)		max(最大)	max(最大)			
10	30	14.3	0.6	7150	3900	730	400	17000	22000	5200	14.5	15	25	0.6	0.05
12	32	15.9	0.6	10500	5800	1070	590	15000	20000	5201	16.7	17	27	0.6	0.06
15	35	15.9	0.6	11700	7050	1190	715	13000	17000	5202	18.3	20	30	0.6	0.07
17	40	17.5	0.6	14600	9050	1490	920	11000	15000	5203	20.8	22	35	0.6	0.09
20	47	20.6	1	19600	12400	2000	1270	10000	13000	5204	24.3	26	41	1	0.12
25	52	20.6	1	21300	14700	2170	1500	8500	11000	5205	26.8	31	46	1	0.19
30	62	23.8	1	29600	21100	3000	2150	7100	9500	5206	31.6	36	56	1	0.29
35	72	27	1.1	39000	28700	4000	2920	6300	8000	5207	36.6	42	65	1	0.43
40	80	30.2	1.1	44000	33500	4500	3400	5600	7100	5208	41.5	47	73	1	0.57
45	85	30.2	1.1	49500	38000	5050	3900	5000	6700	5209	43.4	52	78	1	0.62
50	90	30.2	1.1	53000	43500	5400	4400	4800	6000	5210	45.9	57	83	1	0.67
55	100	33.3	1.5	56000	49000	5700	5000	4300	5600	5211	50.1	64	91	1.5	0.96
60	110	36.5	1.5	69000	62000	7050	6300	3800	5000	5212	56.5	69	101	1.5	1.35
65	120	38.1	1.5	76500	69000	7800	7050	3600	4500	5213	59.7	74	111	1.5	1.65
70	125	39.7	1.5	94000	82000	9600	8400	3400	4500	5214	63.8	79	116	1.5	1.8
75	130	41.3	1.5	93500	83000	9550	8500	3200	4300	5215	66.1	84	121	1.5	1.9
80	140	44.4	2	99000	93000	10100	9500	3000	3800	5216	69.6	90	130	2	2.5
80	150	49.2	2	116000	110000	11800	11200	2800	3600	5217	75.3	95	140	2	3.4