

Bearing Designation	Dimensions									Ball Diameter	Load Rating		Weight
轴承型号	尺寸(mm)									钢球直径	载荷(KN)		重量
	d	B	C1	d1	d2	d3-6g	h	L1	L2		Dynamic Load	Static load	=Kg
	H7										动载	静载	
POS5HD	5	8	6	7.7	18	M5	33	19	42	11.11	3.2	4.3	0.013
POS6HD	6	9	6.75	8.9	20	M6	36	21	46	12.7	4.2	6	0.02
POS8HD	8	12	9	10.3	24	M8	42	25	54	15.87	7.1	11	0.038
POS10HD	10	14	10.5	12.9	28	M10	48	28	63	19.05	9.8	17.4	0.055
POS12HD	12	16	12	15.4	32	M12	54	32	71	22.22	13.2	23.5	0.085
POS14HD	14	19	13.5	16.8	36	M14	60	36	79	25.4	17	28	0.14
POS16HD	16	21	15	19.3	42	M16	66	37	87	28.58	21.4	32	0.21
POS18HD	18	23	16.5	21.8	46	M18X1.5	72	41	95	31.75	26	42.5	0.28
POS20HD	20	25	18	24.3	50	M20x1.5	78	45	103	34.925	31	47.5	0.38
POS22HD	22	28	20	25.8	54	M22x1.5	84	48	112	38.1	42.2	57	0.48
POS25HD	25	31	22	29.5	60	M24x2	94	55	124	42.86	52.7	68	0.64
POS28HD	28	35	24	32.29	66	M27x2	103	62	136	47.63	58.8	79	0.949
POS30HD	30	37	25	34.8	70	M30x2	110	66	145	50.8	70.7	88	1.1