

Bearing Designation	Dimensions(mm/in)										Ball Diameter	Load Rating	Weight
	尺寸(mm/英寸)												
轴承	d+0.038 -0.012	B	C1	d2	d3 UNF-2B	h1	l1	(l2)	d4	SW	钢球直径	载荷(KN)	重量
													≈ kg
SJF4T	6.35	9.53	7.14	20.47	2001/4/28	33.32	15.88	43.55	11.89	9.52	16	21.3	0.026
SJF4T	0.25	0.375	0.281	0.806	2001/4/28	1.312	0.625	1.714	0.468	0.375	16	21.3	0.026
SJF5T	7.938	11.11	8.74	22.86	5/16-24	34.93	17.45	46.35	12.7	11.1	14	26.3	0.041
SJF5T	0.3125	0.437	0.344	0.9	5/16-24	1.375	0.687	1.825	0.5	0.437	14	26.3	0.041
SJF6T	9.525	12.7	10.31	26.03	2003/8/24	41.28	22.22	54.29	17.45	14.27	12	32.7	0.068
SJF6T	0.375	0.5	0.406	1.025	2003/8/24	1.625	0.875	2.13	0.687	0.562	12	32.7	0.068
SJF7T	11.112	14.27	11.1	29.21	7/16-20	46.02	25.4	60.6	19.05	15.88	14	35.2	0.089
SJF7T	0.4375	0.562	0.437	1.15	7/16-20	1.812	1	2.38	0.75	0.625	14	35.2	0.089
SJF8T	12.7	15.88	12.7	33.96	2001/2/20	53.98	28.58	70.96	22.22	19.05	12	55.7	0.149
SJF8T	0.5	0.625	0.5	1.337	2001/2/20	2.125	1.125	2.97	0.875	0.75	12	55.7	0.149
SJF10T	15.875	19.05	17.27	38.74	2005/8/18	63.5	34.93	82.87	25.4	22.22	16	61.6	0.216
SJF10T	0.625	0.75	0.562	1.525	2005/8/18	2.5	1.375	3.262	1	0.875	16	61.6	0.216
SJF12T	19.05	22.23	17.45	45.09	2003/4/16	73.03	41.28	95.57	28.58	25.4	14	96.3	0.327
SJF12T	0.75	0.875	0.687	1.775	2003/4/16	2.875	1.625	3.762	1.125	1	14	96.3	0.327