

Principal dimensions (mm)			Basic load ratings (KN)		Pu	Speed ratings (rpm)		Bearing+ Withdraw	Designation	Dimensions (mm)											Abutment and fillet dimensions (mm)				Value				
基本尺寸			基本额定负荷		疲劳负荷极限	额定转速		轴承+ 退卸套	型号		尺寸											安装尺寸				计算系数			
d ₁	D	B	dyc	stc		Speed Ratings	Limiting Speed		Bearing	Withdrawal sleeves	d ₁	d ₂	D1	B ₁	B ₂ ¹⁾	G	G ₁	b	k	r _{1,2}	d _a	Da	r _a	e	Y1	Y2	Y ₀		
		Cr	Cor	Min	Max			Max			Max																		
400	620	150	3400	6000	415	600	1100	175	*23084CAK/W33	AOH3084G	400	485	563	186	196	Tr440×5	34	22.3	12	5	438	602	4	0.22	3	4.6	2.8		
400	700	224	5600	9300	620	480	900	375	*23184CKJ/W33	AOH3184G	400	483	607	266	276	Tr440×5	40	22.3	12	6	446	674	5	0.30	2.3	3.4	2.2		
420	650	157	3650	6550	450	560	1000	200	*23088CAK/W33	AOHX3088G	420	509	590	194	205	Tr460×5	35	22.3	12	6	463	627	5	0.22	3	4.6	2.8		
440	680	163	3900	6950	465	560	950	225	*23092CAK/W33	AOHX3092G	440	531	617	202	213	Tr480×5	37	22.3	12	6	483	657	5	0.22	3	4.6	2.8		
480	720	167	4150	7800	510	500	900	250	*230/500CAK/W33	AOHX30/500G	480	571	658	209	221	Tr530×6	40	22.3	12	6	523	697	5	0.21	3.2	4.8	3.2		
500	780	185	5100	9300	630	450	800	360	*230/530CAK/W33	AOH30/530	500	611	710	230	242	Tr560×6	45	22.3	12	6	553	757	5	0.22	3	4.6	2.8		
530	820	195	5600	10200	680	430	750	430	*230/560CAK/W33	AOH30/560	530	644	746	240	252	Tr600×6	45	22.3	12	6	583	797	5	0.22	3	4.6	2.8		
570	870	200	6000	11400	750	400	700	480	*230/600CAK/W33	AOHX30/600	570	683	789	245	259	Tr630×6	45	22.3	12	6	623	847	5	0.22	3	4.6	2.8		
600	920	212	6700	12500	800	380	670	575	*230/630CAK/W33	AOH30/630	600	725	839	258	272	Tr670×6	46	22.3	12	7.5	658	892	6	0.21	3.2	4.8	3.2		
630	980	230	7650	14600	915	340	600	720	*230/670CAK/W33	AOH30/670	630	770	892	280	294	Tr710×7	50	22.3	12	7.5	698	952	6	0.21	3.2	4.8	3.2		
710	1090	250	9650	18600	1100	300	530	950	*230/750CAK/W33	AOH30/750	710	860	998	300	316	Tr800×7	50	22.3	12	7.5	778	1062	6	0.21	3.2	4.8	3.2		
750	1150	258	10000	20000	1160	280	480	1100	*230/800CAK/W33	AOH30/800	750	915	1053	308	326	Tr850×7	50	22.3	12	7.5	828	1122	6	0.20	3.4	5	3.2		
800	1220	272	9370	21600	1270	240	450	1250	230/850CAK/W33	AOH30/850	800	969	1117	325	343	Tr900×7	53	22.3	12	7.5	878	1192	6	0.20	3.4	5	3.2		
850	1280	280	10100	23200	1340	220	400	1450	230/900CAK/W33	AOH30/900	850	1023	1176	335	355	Tr950×8	55	22.3	12	7.5	928	1252	6	0.20	3.4	5	3.2		
900	1360	300	12000	28500	1600	200	380	1720	230/950CAK/W33	AOH30/950	900	1083	1246	355	375	Tr1000×8	55	22.3	12	7.5	978	1332	6	0.20	3.4	5	3.2		
950	1420	308	12700	30500	1700	180	360	1900	230/1000CAK/W33	AOH30/1000	950	1139	1305	365	387	Tr1060×8	57	22.3	12	7.5	1028	1392	6	0.19	3.6	5.3	3.6		
1000	1500	325	13800	34000	1830	170	320	2600	230/1060CAK/W33	AOH30/1060	1000	1202	1378	385	407	Tr1120×8	60	22.3	12	9.5	1094	1466	8	0.19	3.6	5.3	3.6		