

Principal dimensions (mm)			Basic load ratings (KN)		Pu	Speed ratings (rpm)		Weight (kg)	Designation	Dimensions (mm)						Abutment and fillet dimensions (mm)			Value				Accelerated speed (rotating/linear)	
基本尺寸			基本额定负荷		疲劳寿命限制	额定转速		重量	型号	尺寸						安装尺寸			计算系数				加速速率	
d _t	D	B	dyc Cr	stc Cor		Speed Ratings	Limiting Speed			Cylindrical Bore	Taper Bore	d	d2~	D1~	b	k	r1,2 Min	da Min	Da Max	ra Max	e	Y1		Y2
40	90	33	150	140	15	6000	8000	1.10	*22308E/VA405	-	40	49.7	74.3	5.5	3	1.5	49	81	1.5	0.37	1.8	2.7	1.8	115g
45	100	36	183	183	19.6	5300	7000	1.40	*22309E/VA405	-	45	56.4	83.4	5.5	3	1.5	54	91	1.5	0.37	1.8	2.7	1.8	97g
50	110	40	220	224	24	4800	6300	1.90	*22310E/VA405	-	50	62.1	91.9	5.5	3	2	61	99	2	0.37	1.8	2.7	1.8	85g
55	120	43	270	280	30	4300	5600	2.45	*22311E/VA405	*22311EK/VA405	55	70.1	102	5.5	3	2	66	109	2	0.35	1.9	2.9	1.8	78g
60	130	46	310	335	36.5	4000	5300	3.10	*22312E/VA405	*22312EK/VA405	60	77.9	110	8.3	4.5	2.1	72	118	2	0.35	1.9	2.9	1.8	70g
65	140	48	340	360	38	3800	5000	3.75	*22313E/VA405	*22313EK/VA405	65	81.6	118	8.3	4.5	2.1	77	128	2	0.35	1.9	2.9	1.8	69g
70	150	51	400	430	45	3400	4500	4.55	*22314E/VA405	*22314EK/VA405	70	90.3	128	8.3	4.5	2.1	82	138	2	0.33	2	3	2	61g
75	160	55	440	475	48	3200	4300	5.55	*22315E/VA405	*22315EK/VA405	75	92.8	135	8.3	4.5	2.1	87	148	2	0.35	1.9	2.9	1.8	88g
80	170	58	490	540	54	3000	4000	6.60	*22316E/VA405	*22316EK/VA405	80	98.3	143	8.3	4.5	2.1	92	158	2	0.35	1.9	2.9	1.8	80g
85	180	60	550	620	61	2800	3800	7.65	*22317E/VA405	*22317EK/VA405	85	108	154	8.3	4.5	3	99	166	2.5	0.33	2	3	2	74g
85	180	60	550	620	61	2800	3800	7.65	*22317E/VA406	-	85	108	154	8.3	4.5	3	99	166	2.5	0.33	2	3	2	74g
90	190	64	610	695	67	2600	3600	9.05	*22318E/VA405	*22318EK/VA405	90	113	161	11.1	6	3	104	176	2.5	0.33	2	3	2	68g
95	200	67	670	765	73.5	2600	3400	10.5	*22319E/VA405	*22319EK/VA405	95	118	168	11.1	6	3	109	186	2.5	0.33	2	3	2	64g
100	215	73	815	950	88	2400	3000	13.5	*22320E/VA405	*22320EK/VA405	100	130	184	11.1	6	3	114	201	2.5	0.33	2	3	2	56g
100	215	73	815	950	88	2400	3000	13.5	*22320E/VA406	-	100	130	184	11.1	6	3	114	201	2.5	0.33	2	3	2	56g
110	240	80	950	1120	100	2000	2800	18.4	*22322E/VA405	*22322EK/VA405	110	143	204	13.9	7.5	3	124	226	2.5	0.33	2	3	2	53g
110	240	80	950	1120	100	2000	2800	18.4	*22322E/VA406	-	110	143	204	13.9	7.5	3	124	226	2.5	0.33	2	3	2	53g
120	260	86	965	1120	100	2000	2600	23.0	*22324CCJAW33VA405	*22324CCKJAW33VA405	120	152	216	13.9	7.5	3	134	246	2.5	0.35	1.9	2.9	1.8	96g
120	260	86	965	1120	100	2000	2600	23.0	*22324CCJAW33VA406	-	120	152	216	13.9	7.5	3	134	246	2.5	0.35	1.9	2.9	1.8	96g
130	280	93	1120	1320	114	1800	2400	29.0	*22326CCJAW33VA405	*22326CCKJAW33VA405	130	164	233	16.7	9	4	147	263	3	0.35	1.9	2.9	1.8	87g
130	280	93	1120	1320	114	1800	2400	29.0	*22326CCJAW33VA406	-	130	164	233	16.7	9	4	147	263	3	0.35	1.9	2.9	1.8	87g
140	300	102	1290	1560	132	1700	2200	36.5	*22328CCJAW33VA405	*22328CCKJAW33VA405	140	175	247	16.7	9	4	157	283	3	0.35	1.9	2.9	1.8	78g
140	300	102	1290	1560	132	1700	2200	36.5	*22328CCJAW33VA406	-	140	175	247	16.7	9	4	157	283	3	0.35	1.9	2.9	1.8	78g
150	320	108	1460	1760	146	1600	2000	43.5	*22330CCJAW33VA405	*22330CCKJAW33VA405	150	188	266	16.7	9	4	167	303	3	0.35	1.9	2.9	1.8	72g
150	320	108	1460	1760	146	1600	2000	43.5	*22330CCJAW33VA406	-	150	188	266	16.7	9	4	167	303	3	0.35	1.9	2.9	1.8	72g
160	340	114	1600	1960	160	1500	1900	52.0	*22332CCJAW33VA405	*22332CCKJAW33VA405	160	200	282	16.7	9	4	177	323	3	0.35	1.9	2.9	1.8	69g
160	340	114	1600	1960	160	1500	1900	52.0	*22332CCJAW33VA406	-	160	200	282	16.7	9	4	177	323	3	0.35	1.9	2.9	1.8	69g
170	360	120	1760	2160	176	1400	1800	61.0	*22334CCJAW33VA405	*22334CCKJAW33VA405	170	213	300	16.7	9	4	187	343	3	0.33	2	3	2	65g
170	360	120	1760	2160	176	1400	1800	61.0	*22334CCJAW33VA406	-	170	213	300	16.7	9	4	187	343	3	0.33	2	3	2	65g
180	380	126	2000	2450	193	1300	1700	71.5	*22336CCJAW33VA405	*22336CCKJAW33VA405	180	224	317	22.3	12	4	197	363	3	0.35	1.9	2.9	1.8	59g
180	380	126	2000	2450	193	1300	1700	71.5	*22336CCJAW33VA406	-	180	224	317	22.3	12	4	197	363	3	0.35	1.9	2.9	1.8	59g
190	400	132	2120	2650	208	1200	1600	82.5	*22338CCJAW33VA405	*22338CCKJAW33VA405	190	236	333	22.3	12	5	210	380	4	0.35	1.9	2.9	1.8	57g
190	400	132	2120	2650	208	1200	1600	82.5	*22338CCJAW33VA406	-	190	236	333	22.3	12	5	210	380	4	0.35	1.9	2.9	1.8	57g
200	420	138	2320	2900	224	1200	1500	95.0	*22340CCJAW33VA405	*22340CCKJAW33VA405	200	248	351	22.3	12	5	220	400	4	0.33	2	3	2	55g
200	420	138	2320	2900	224	1200	1500	95.0	*22340CCJAW33VA406	-	200	248	351	22.3	12	5	220	400	4	0.33	2	3	2	55g
220	460	145	2700	3450	260	1000	1400	120	*22344CCJAW33VA405	*22344CCKJAW33VA405	220	279	389	22.3	12	5	240	440	4	0.31	2.2	3.3	2.2	49g
240	500	155	3100	4000	290	950	1300	155	*22348CCJAW33VA405	*22348CCKJAW33VA405	240	303	423	22.3	12	5	260	480	4	0.31	2.2	3.3	2.2	45g