

Bearing Designation	Dimensions(mm/in)										Ball Diameter	Load Rating	Weight
轴承型号	尺寸(mm/英寸)										钢球直径	载荷(KN)	重量
	d+0.03	B	C1	d2	d3	h1	L3	(L4)	d4	sw			≈ kg
	-0.01				UNF-2B								
SCF3T	4.826	7.92	5.94	15.88	10-32	26.97	11.11	34.91	10.31	7.92	13	5.8	
SCF3T	0.19	0.312	0.234	0.625	10-32	1.062	0.437	1.375	0.406	0.312	13	5.8	0.018
SCF4T	6.35	9.53	6.35	19.05	4/28	33.32	14.28	42.85	11.89	9.52	18	8.2	0.022
SCF4T	0.25	0.375	0.25	0.75	4/28	1.312	0.562	1.687	0.468	0.375	18	8.2	0.022
SCF5T	7.938	11.1	7.92	22.23	5/16	34.92	15.88	46.03	12.7	11.1	14	10.2	0.036
SCF5T	0.3125	0.437	0.312	0.875	5/16	1.375	0.625	1.812	0.5	0.437	14	10.2	0.036
SCF6T	9.525	12.7	9.11	25.4	8/24	41.28	19.05	53.98	17.45	14.27	14	14	0.059
SCF6T	0.375	0.5	0.359	1	8/24	1.625	0.75	2.125	0.687	0.562	14	14	0.059
SCF7T	11.112	14.27	10.31	28.58	7/16	46.02	22.22	60.3	19.05	15.88	13	17.6	0.081
SCF7T	0.4375	0.562	0.406	1.125	7/16	1.812	0.875	2.375	0.75	0.625	13	17.6	0.081
SCF8T	12.7	15.88	11.5	33.32	2/20	53.98	25.4	70.64	22.22	19.05	12	23.7	0.131
SCF8T	0.5	0.625	0.453	1.312	2/20	2.125	1	2.781	0.875	0.75	12	23.7	0.131
SCF10T	15.875	19.05	12.29	38.1	8/18	63.5	31.75	82.55	25.4	22.22	16	25.7	0.195
SCF10T	0.625	0.75	0.484	1.5	8/18	2.5	1.25	3.25	1	0.875	16	25.7	0.195
SCF12T	19.05	22.23	15.06	44.45	4/16	73.03	38.1	95.25	28.58	25.4	14	42.4	0.294
SCF12T	0.75	0.875	0.593	1.75	4/16	2.875	1.5	3.75	1.125	1	14	42.4	0.294