

Type	Rail Size						Load capacity					Weight	
轴承型号	轨道尺寸						载重					重量	
	Width	Height	Pitch	Bolt Hole	G	Max.length Of rail	Dynamic	Sationary	Stationary moment(kgf.M)	Stationary moment (kgf.M)	Stationary moment (kgf.M)	bearing	rail
	宽度	高度	节径	螺栓孔		最大轨道长度	动载荷	静载荷	静	动	动	轴承	轨道
	W1	H1	F	d×D×h	Lomax	C(kgf)	Co(kgf)	MRO	MPO	MrO	(kgf)	(kgf/M)	
SBG15SL	15	15	60	45*7.5*5.3	20	1600	840	1370	7	5	5	0.14	1.5
SBG20SL	20	17.5	60	6*9.5*8.5	20	3040	1400	2420	22	18	18	0.36	2.16
SBG25SL	23	21.8	60	7*11*9	20	4480	2020	3500	36	32	31	0.44	3.14
SBG30SL	28	25	80	9*14*12	20	4440	2360	3970	50	36	36	0.72	4.5
SBG35SL	34	29	80	9*14*12	20	4440	3800	6230	96	75	73	1.14	6.3
SBG45SL	45	38	105	14*20*17	22.5	4450	6120	9750	216	170	168	2	10.9
SBG55SL	53	45	120	16*23*20	30	4480	9020	13970	367	293	288	4.2	14.9
SBG65SL	63	58.5	150	18*26*22	35	4390	14380	21900	629	495	484	6.15	21.3