

型号	额定扭矩	最大容许误差			最高转速 [min-]	扭转弹性 常数	轴向弹性 常数	转动惯量	质量 [kg]	D	L	d1 . d2	N1.N2	LF	LP	S	C	d3	K	H	M	M1	M2
		偏心	偏角	轴向位移																			
Designation	Rated torque	Eccentricity [mm]	Deflection [°]	Axial displacement[mm]	Max rotating speed	Torsional elasticity constant	Axial elastic constant	Rotational inertia	Weight														
LC-BF-070DS	70	0.25	1(单膜片)	±1.0	14000	30000	53	0.83x10-3	1.14	70	78	18 . 19	53	23.5	8	6.5	5	35	31	4-5.1	M6	4-M6	2-M6
LC-BF-080DS	130	0.31	1(单膜片)	±1.0	13000	32000	48	1.36x10-3	1.57	80	87.6	28 . 30	63	25.5	10	8.3	5	40	37	4-5.1	M8	4-M6	2-M6
LC-BF-090DS	200	0.3	1(单膜片)	±1.2	12000	70000	160	2.58x10-3	2.03	90	86.4	38 . 40	78	25.5	10	7.7	5	50	50	3-6.8	M8	6-M6	3-M6
LC-BF-100DS	300	0.31	1(单膜片)	±1.4	10000	80000	180	3.76x10-3	2.27	100	87	42 . 45	83	25.5	10	8	5	60	58	3-6.8	M8	6-M6	3-M6
LC-BF-120DS	500	0.38	1(单膜片)	±1.6	9000	70000	180	3.76x10-3	3.46	120	97.4	48.50.52	88	27.5	12	10.2	5	72	68	3-8.6	M10	6-M6	3-M6
LC-BF-140DS	800	0.44	1(单膜片)	±2.0	8000	50000	180	3.76x10-3	6.06	140	120.2	50.52.55	98	36.5	15	10.6	5.5	80	78	3-8.6	M12	6-M8	3-M8