

型号	额定扭矩 [N·m]	最大容许误差			最高转速 [min-1]	扭转弹性 常数	轴向弹性 常数	转动惯量	质量 [kg]											
Designation	Rated torque	偏心	偏角	轴向位移	Max rotating speed	Torsional elasticity constant	Axial elastic constant	Rotational inertia	Weight	D	L	d1 . d2	N1.N2	LF	S	K	H	M	M1	M2
		Eccentricity [mm]	Deflection [°]	Axial displacement [mm]																
LC-BM-090SS	200	0.02	1	±0.6	20000	140000	320	1.87x10-3	1.66	90	75.7	32 . 35	78	34	1.1	50	3-6.8	M8	6-M6	3-M6
LC-BM-100SS	300	0.02	1	±0.7	20000	160000	360	3.56x10-3	2.07	100	76	50 . 52	93	34	1	58	3-6.8	M8	6-M6	3-M6
LC-BM-120SS	500	0.02	1	±0.8	20000	140000	360	6.65x10-3	2.9	120	82.2	55	98	36	1	68	3-8.6	M10	6-M6	3-M6
LC-BM-140SS	800	0.02	1	±1.0	20000	100000	360	16.9x10-3	5.35	140	100.6	60 . 62	115	45	1	78	3-8.6	M12	6-M8	3-M8