

轴承型号	外形尺寸				有关安装尺寸(mm)		重量	
Designation	Dimensions				Mounting dimensions		Weight	
	d	D	B	r min	d1	D1	(kg)	
	(mm)				最小 min	最大 max	ZrO2	Si3N4
51100CE	10	24	9	0.3	24	11	0.015	0.0078
51200CE	10	26	11	0.6	26	12	0.022	0.011
51101CE	12	26	9	0.3	26	13	0.016	0.009
51201CE	12	28	11	0.6	28	14	0.024	0.013
51102CE	15	28	9	0.3	28	16	0.018	0.0094
51202CE	15	32	12	0.6	32	17	0.033	0.018
51103CE	17	30	9	0.3	30	18	0.019	0.01
51203CE	17	35	12	0.6	35	19	0.038	0.021
51104CE	20	35	10	0.3	35	21	0.028	0.015
51204CE	20	40	14	0.6	40	22	0.059	0.032
51105CE	25	42	11	0.6	42	26	0.043	0.023
51205CE	25	47	15	0.6	47	27	0.085	0.046
51106CE	30	47	11	0.6	47	32	0.049	0.026
51206CE	30	52	16	0.6	52	32	0.11	0.056
51107CE	35	52	12	0.6	52	37	0.062	0.033
51207CE	35	62	18	1	62	37	0.16	0.086
51108CE	40	60	13	0.6	60	42	0.092	0.049
51208CE	40	68	19	1	68	42	0.21	0.11
51109CE	45	65	14	0.6	65	47	0.11	0.059
51209CE	45	73	20	1	73	47	0.24	0.13
51110CE	50	70	14	0.6	70	52	0.12	0.063
51210CE	50	78	22	1	78	52	0.29	0.16
51111CE	55	78	16	0.6	78	57	0.17	0.093
51211CE	55	90	25	1	90	57	0.46	0.25
51112CE	60	85	17	1	85	62	0.22	0.12
51212CE	60	95	26	1	95	62	0.52	0.28
51113CE	65	90	18	1	90	67	0.25	0.13
51213CE	65	100	27	1	100	67	0.58	0.31
51114CE	70	95	18	1	95	72	0.27	0.14
51214CE	70	105	27	1	105	72	0.61	0.33
51115CE	75	100	19	1	100	77	0.3	0.16
51215CE	75	110	27	1	110	77	0.65	0.35
51116CE	80	105	19	1	105	82	0.32	0.17
51216CE	80	115	28	1	115	82	0.72	0.38
51117CE	85	110	19	1	110	87	0.34	0.18
51217CE	85	125	31	1	125	88	0.94	0.5
51118CE	90	120	22	1	120	92	0.5	0.27
51218CE	90	135	35	1.1	135	93	1.3	0.69
51120CE	100	135	25	1	135	102	0.74	0.39
51220CE	100	150	38	1.1	150	103	1.73	0.92
51122CE	110	145	25	1	145	112	0.8	0.43
51124CE	120	155	25	1	155	122	0.86	0.46