

Bearing Designation	maximum torque	Differential rotation of the air resistance	The maximum idle speed		The biggest inching frequency	Size			Shaft diameter	keyway	With bearing	Weight
型号	最大扭矩	差速转动时的空气阻力	最大空转转速 (ffmin)		最大寸动频率	+0	B		轴径	键槽	配套使用轴承	重量
	(N.m)	(N-m)	Bearing 轴承	Outer race 外座圈	(次/min)	A(x_0.06 )			C -0.025		JIS标准	(kg)
B203	39.2	0.098	2,400	500	150	25	40	-0.039	16.51	4X2.5	6203	0.23
B204	58.8	0.098	2,400	500	150	25	47	-0.039	18.796	5X3	6204	0.34
B205	98	0.196	1,800	400	150	25	52	-0.042	23.622	5X3	6205	0.45
B206	235	0.196	1,800	350	150	28	62	-0.042	32.766	7X4	6206	0.68
B207	372	0.196	1,800	300	150	28	72	-0.042	42.088	7X4	6207	0.8
B208	549	0.196	1,800	200	150	32	80	-0.042	46.761	10X4.5	6208	0.91
B209	549	0.196	1,800	200'	150	32	85	-0.045	46.761	10X4.5	6209	0.95
B210	784	0.294	1,200	200	150	32	90	-0.045	56.109	10X4.5	6210	1
B211	784	0.294	1,200	200	150	32	100	-0.05	56.109	10X4.5	6211	1.4
B212	1,230	0.294	1,200	180	150	42	110	-0.05	70.029	10X4.5	6212	1.8
B213	1,230	0.294	1,200	180	150	42	120	-0.05	70.029	10X4.5	6213	2.3
B214	1,390	0.392	1,000	180	150	42	125	-0.06	79.356	12X4.5	6214	2.4