

Bearing Number	Size		Overrunning speeds	D	L ₁	F	E	B	N	L	b ^{H11}	Weight
	尺寸		极限速度									重量
型号	d _{H7}	T _{KN}	n _{imax}	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(Kg)
	(mm)	(Nm)	min ⁻¹									
RSBW20	20	375	400	106	35	113	102,5	40	35	15	18	2
RSBW25	25	606	400	106	48	113	102,5	40	35	15	18	2,6
RSBW30	30	606	400	106	48	113	102,5	40	35	15	18	2,5
RSBW35M	35M	375	400	106	35	113	102,5	40	35	15	18	2
RSBW35	35	606	400	106	48	113	102,5	40	35	15	18	2,4
RSBW40	40	1295	300	132	52	125	115	60	35	15	18	4,6
RSBW45	45	1295	300	132	52	125	115	60	35	15	18	4,5
RSBW50	50	1295	300	132	52	125	115	60	35	15	18	4,5
RSBW55	55	1295	300	132	52	125	115	60	35	15	18	4,4
RSBW60	60	2550	250	161	54	140	130	70	35	15	18	6,5
RSBW70	70	2550	250	161	54	140	130	70	35	15	18	6,4
RSBW80	80	4875	200	190	70	165	150	70	45	20	25	9,9
RSBW90	90	4875	200	190	70	165	150	70	45	20	25	9,8