

带座轴承代号	外形尺寸 (mm) Dimensions (mm)								重量 (kg)	额定动负荷	额定静负荷	极限转速
Designation	d	D	B	PL	C	r/min	G	dPL	Weight	Basic load ratings cr(KN)	Basic load ratings cor(KN)	Limiting Speed(r/min)
SSB201	12	47	31	13	17	0.6	4.5	M6 x 1	0.0377	9.97	6.22	4000
SSB202	15	47	31	13	17	0.6	4.5	M6 x 1	0.0341	9.97	6.22	4000
SSB203	17	47	31	13	17	0.6	4.5	M6 x 1	0.0323	9.97	6.22	4000
SSB204	20	47	31	13	17	1	4.5	M6 x 1	0.0287	9.88	6.2	4000
SSB205	25	52	34	14	17V	1	5	M6 x 1	0.0395	10.78	6.98	3400
SSB206	30	62	38	16	19	1	5	M6 x 1	0.0628	14.97	10.04	2800
SSB207	35	72	43	18	20	1.1	6	M8 x 1	0.0933	19.75	13.67	2400
SSB208	40	80	49	19	21	1.1	8	M8 x 1	0.1256	22.71	15.94	2200
SSB209	45	85	49	19	22	1.1	8	M8 x 1	0.1328	24.36	17.71	1900
SSB210	50	90	52	19	24	1.1	9	M10 x 1	0.149	26.98	19.84	1800
SSB211	55	100	56	22	25	1.5	9	M10 x 1	0.2082	33.37	15.11	1600
SSB212	60	110	65	25	27	1.5	10	M10 x 1	0.28	36.74	27.97	1500
SSB213	65	120	65	25	27	1.5	10	M10 x 1	0.3518	44.01	34.18	1400
SSB214	70	125	75	30	29	1.5	12	M12 x 1.25	0.3913	46.79	37.59	1300
SSB215	75	130	78	33	30	1.5	12	M12 x 1.25	0.4344	50.85	41.26	1200
SSB216	80	140	83	33	33	2	14	M12 x 1.25	0.5062	55.04	45.09	1100
SSB217	85	150	86	34	36	2	14	M12 x 1.25	0.6103	64.01	53.28	1000
SSB218	90	160	96	40	37	2	14	M12 x 1.25	0.7718	73.83	60.76	950
SSB220	100	180	108	42	41	2	14	M12 x 1.25	0.8077	93.95	79.35	900