

Principal dimensions				Basic load ratings		Basic load ratings		Limiting Speed		Designation	Distance of action point	Installation dimensions			Weight
外形尺寸				额定载荷		额定载荷		极限转速		轴承代号	作用点距离	安装尺寸 (mm)			重量
d	D	B	r	Cr	Cor	Cr	Cor	(rpm)			a ₀	d _a	Da	r _a	(kg)
			min(最小)	(N)		{kgf}		脂润滑	油润滑		(mm)	min(最小)	max(最大)	max(最大)	
30	72	19	1.1	46000	63000	4700	6450	8000	11000	QJ306	35.7	37	65	1	0.42
35	80	21	1.5	55000	80000	5600	8150	7100	9500	QJ307	40.3	44	71	1.5	0.57
40	90	23	1.5	67000	100000	6850	10200	6300	8500	QJ308	45.5	49	81	1.5	0.78
45	100	25	1.5	87500	133000	8900	13500	5600	7500	QJ309	50.8	54	91	1.5	1.05
50	110	27	2	102000	159000	10400	16200	5000	6700	QJ310	56	60	100	2	1.35
55	120	29	2	118000	187000	12000	19100	4500	6300	QJ311	61.3	65	110	2	1.75
60	130	31	2.1	135000	217000	13800	22200	4300	5600	QJ312	66.5	72	118	2	2.15
65	140	33	2.1	153000	250000	15600	25500	3800	5300	QJ313	71.8	77	128	2	2.7
70	150	35	2.1	172000	285000	17500	29100	3600	5000	QJ314	77	82	138	2	3.18
75	160	37	2.1	187000	320000	19100	33000	3400	4800	QJ315	82.3	87	148	2	3.9
80	170	39	2.1	202000	360000	20600	37000	3200	4300	QJ316	87.5	92	158	2	4.6
85	180	41	3	218000	405000	22300	41000	3000	4000	QJ317	92.8	99	166	2.5	5.34
90	190	43	3	235000	450000	23900	45500	2800	3800	QJ318	98	104	176	2.5	6.4
95	200	45	3	251000	495000	25600	50500	2600	3600	QJ319	103.3	109	186	2.5	7.4