

Dimensions(mm)				Basic load ratings(KN)		Limiting Speed (rpm)		Designation	Weight(Kg)
外形尺寸(毫米)				基本额定负荷 (千牛)		极限转速(转/分)		型号	重量 (千克)
						Grease 脂润滑	Oil 油润滑		
d	D	B	rmin	Cr	Cor				
100	140	20	1.1	30.9	37.8	3700	4900	61920M	0.92
110	150	20	1.1	31.6	40.3	3400	4500	61922M	1
120	165	22	1.1	39.2	50.9	3000	4000	61924M	1.4
130	180	24	1.5	48.2	63.5	2800	3700	61926M	1.8
140	190	24	1.5	51	71	2600	3400	61928M	2
150	210	28	2	62.7	85.2	2300	3100	61930M	3.2
155	215	28	2	62.4	85.3	2300	3000	61931M	3.2
160	220	28	2	64.5	90.5	2200	2900	61932M	3.3
170	230	28	2	68	100	2000	2700	61934M	3.44
180	250	33	2	84.6	119	1900	2500	61936M	4.8
190	240	24	1.5	54.6	84.2	1900	2500	61838M	2.8
190	260	33	2	90	133	1800	2400	61938M	5.2
190	269.5	33	2	90	133	1700	2300	61938X1M	6.3
200	250	24	1.5	55.5	87.6	1800	2400	61840M	3
200	279.5	38	2.1	110	180	1600	2200	61940X1-1M	7.3
200	280	38	2.1	110	158	1600	2200	61940M	7.39
200	289.5	38	2.1	110	158	1600	2200	61940X1-2M	8.7
220	270	24	1.5	57.3	94.2	1600	2200	61844M	3.2
220	300	38	2.1	105	162	1500	2000	61944M	8.2
220	309.5	38	3	116	178	1450	1930	61944X1M	9.48
230	329.5	40	3	1389	215	1350	1800	61946X3M	11.7
240	300	28	2	73.6	122	1400	1860	61848M	4.8
240	320	38	2.1	119	186	1350	1800	61948M	8.6
250	359.5	46	2.1	157	254	1200	1600	61950X1M	16
260	320	28	2	76	131	1300	1720	61852M	5.2
260	360	46	2.1	163	269	1180	1570	61952M	14.9
260	369.5	46	2.1	163	269	1150	1530	61952X1-2M	16.5
260	370	46	2.1	163	269	1150	1530	61952X1-1M	16.6
280	350	33	2	99.8	170	1150	1530	61856M	7.6
280	380	46	2.1	168	285	1080	1440	61956M	15.3
280	389.5	46	2.1	167	285	1060	1420	61956X1-2M	17.8
280	390	46	2.1	167	285	1060	1420	61956X1-1M	17.9
320	400	38	2.1	115	205	960	1290	61864M	11.2
320	440	56	3	212	394	900	1220	61964M	26.2
340	420	38	2.1	119	219	900	1220	61868M	11.7
340	460	56	3	218	418	850	1130	61968M	27.2
360	440	38	2.1	120	226	850	1130	61872M	12.5
360	480	56	3	223	438	820	1080	61972M	28.5
380	480	46	2.1	178	337	800	1050	61876M	20
380	520	65	4	250	505	760	1000	61976M	40
400	500	46	2.1	181	350	760	1000	61880M	20.5
400	540	65	4	256	533	720	950	61980M	41.5
420	520	46	2.1	183	363	720	950	61884M	21.5
420	560	65	4	262	558	690	900	61984M	43