

外形尺寸(毫米)					基本额定负荷 (千牛)		极限转速 (转/分)		型号 Designations	重量 (千克)	相当于国外型号(参考) foreign models (reference)	
Boundary dimensions					Basic load ratings(kN)		Speed rating			Weight		
d	D	B	Fw	rmin	Cr	Cor	脂润滑	油润滑		(kg)	SKF	FAG
(mm)							Grease	Oil				
100	140	40	113	1.1	130	280	3400	4200	NNU4920	2.1	NNU4920	NNU4920
110	150	40	123	1.1	140	290	3100	3850	NNU4922	2.2	NNU4922	NNU4922
120	165	45	134.5	1.1	180	340	2800	3500	NNU4924	2.8	NNU4924	NNU4924
120	190	80	141	2	370	710	2500	3100	NNU4124X2	9	-	-
120	215	86	139	2.1	570	850	2200	2750	NNU4224X1	13.6	-	-
130	180	50	146	1.5	220	470	2500	3100	NNU4926	4	NNU4926	NNU4926
140	190	50	156	1.5	280	580	2200	2750	NNU4928	4.2	NNU4928	NNU4928
140	210	62.5	158	2	370	700	2100	2600	NNU4028X1-1	7.9	-	-
140	210	77.5	158	2	450	950	2100	2600	NNU4028X1-2	9.8	-	-
150	210	60	168.5	2	340	730	2000	2500	NNU4930	6.7	NNU4930	NNU4930
150	270	120	180	3	930	1710	1600	2000	NNU4230X1	31.5	-	-
160	220	60	178.5	2	330	680	1900	2350	NNU4932	6.9	NNU4932	NNU4932
170	230	60	188.5	2	340	700	1800	2200	NNU4934	7.25	NNU4934	NNU4934
180	250	69	202	2	400	850	1600	2000	NNU4936	10.5	NNU4936	NNU4936
190	260	69	212	2	420	990	1450	1800	NNU4938	11.5	NNU4938	NNU4938
200	280	80	225	2.1	480	1040	1400	1700	NNU4940	15	NNU4940	NNU4940
200	310	109	234	2.1	670	1440	1350	1700	NNU4040	32.7	-	-
200	310	130	229	2.1	1000	2270	1350	1700	NNU4940X2	38.9	-	-
200	360	148	242	4	1520	2890	1000	1250	NNU4240X1	71.9	-	-
220	300	80	245	2.1	530	1150	1300	1600	NNU4944	18	NNU4944	NNU4944
240	320	80	265	2.1	620	1450	1200	1500	NNU4948	18.5	NNU4948	NNU4948
260	360	100	292	2.1	750	1900	1100	1350	NNU4952	35.8	NNU4952	NNU4952
260	370	100	292	2.1	830	2050	1100	1350	NNU4952X2	37.1	-	-
280	380	100	312	2.1	850	2100	1000	1250	NNU4956	36	NNU4956	NNU4956
300	420	118	339	3	950	2500	900	1150	NNU4960	54.5	NNU4960	NNU4960
320	440	118	359	3	1000	2700	850	1100	NNU4964	58	NNU4964	NNU4964