

外形尺寸(毫米)				基本额定负荷(千牛)		极限转速(转/分)		型号	重量	相当于国外型号(参考)	
Boundary dimensions				Basic load ratings		Speed rating			(千克)	foreign models (reference)	
d	D	B	rmin	Cr	Cor	脂润滑	油润滑	Designations	Weight	SKF	FAG
(mm)				(kN)		Grease	Oil		(kg)		
140	210	69	2	124	217	1800	2400	4028D	10.1	-	-
150	225	75	2.1	159	280	1600	2200	4030D	10.8	-	-
160	240	80	2.1	171	305	1500	2000	4032D	13	-	-
170	260	90	2.1	208	385	1400	1900	4034D	18.1	-	538853
180	280	100	2.1	240	451	1300	1800	4036D	23.6	-	-
190	290	100	2.1	247	480	1200	1700	4038D	24.6	-	-
200	310	109	2.1	273	558	1100	1600	4040D	31.7	-	-
220	340	118	3	309	670	1060	1400	4044D	41.4	-	-
240	360	118	3	315	706	1000	1300	4048D	44.3	-	-
260	400	140	4	376	901	890	1200	4052D	68	-	-
280	420	140	4	383	947	850	1100	4056D	72	-	-
300	460	160	4	425	1098	770	1060	4060D	103	-	-
320	480	160	4	432	1142	740	1000	4064D	109	-	-
340	520	180	5	480	1280	700	900	4068D	135	-	-