

外形尺寸(毫米)				基本额定负荷(千牛)		极限转速(转/分)		型号	重量	相当于国外型号(参考)			
Boundary dimensions				Basic load ratings		Speed rating			(千克)	foreign models (reference)			
d	D	B	rmin	Cr	Cor	脂润滑	油润滑		Designations	Weight	SKF	FAG	NSK
(mm)				(kN)		Grease Oil		(kg)					
100	149.5	24	1.5	80	100	2600	3600	QJF1020X1	1.55				
100	150	24	1.5	80	100	2600	3600	QJF1020	1.55				
110	169.5	28	2	110	140	2300	3100	QJF1022X1	2.5				
110	170	28	2	110	140	2300	3100	QJF1022	2.5				
110	200	38	2.1	239	275	2100	2900	QJF222	5.6	QA110	QA110		
110	240	50	3	328	387	1800	2600	QJF322	12.5				
120	179.5	28	2	115	150	2100	2900	QJF1024X1	2.8				
120	180	28	2	115	150	2100	2900	QJF1024	2.8				
120	215	40	2.1	257	306	1900	2700	QJF224	6.95	QA120	QA120		
120	260	55	3	351	441	1600	2200	QJF324	15.6				
130	199.5	33	2	145	195	1900	2700	QJF1026X1	4.13				
130	200	33	2	145	195	1900	2700	QJF1026	4.13				
130	230	40	3	266	329	1800	2600	QJF226	7.75	QA130	QA130		
130	280	58	4	381	504	1500	2000	QJF326	19.5				
140	209.5	33	2	160	205	1800	2600	QJF1028X1	4.21				
140	210	33	2	160	205	1800	2600	QJF1028	4.21				
140	250	42	3	293	396	1600	2200	QJF228	9.9	QA140	QA140		
140	300	62	4	421	576	1300	1800	QJF328	24				
145	225	40	2.1	180	305	1700	2400	QJF1029X2	6.4				
150	224.5	35	2.1	170	230	1600	2200	QJF1030X1	5.2				
150	225	35	2.1	170	230	1600	2200	QJF1030	5.2				
150	270	45	3	304	419	1500	2000	QJF230	12.5	QA150	QA150		
150	320	65	4	444	639	1100	1500	QJF330	29				
160	239.5	38	2.1	220	300	1500	2000	QJF1032X1	6.36				
160	240	38	2.1	220	300	1500	2000	QJF1032	6.36				
160	290	48	3	351	513	1300	1800	QJF232	15.5	QA160	QA160		
160	340	68	4	486	734	1000	1400	QJF332	34.5				
170	259.5	42	2.1	225	315	1400	1900	QJF1034X1-1	8.4				
170	260	42	2.1	225	315	1400	1900	QJF1034	8.4				
170	265	42	2.1	225	315	1400	1900	QJF1034X1-2	9.4				
180	249.5	33	2	175	345	1300	1800	QJF1936X1	4.8				
180	259.5	52	2.1	170	330	1300	1800	QJF3936X1	9.3				
180	280	46	2.1	250	365	1200	1600	QJF1036	11				
180	320	52	4	392	612	1000	1400	QJF236	20.5	QA180	QA180		
190	269.5	55	2	200	395	1200	1600	QJF3938X1	10.5				
190	289.5	46	2.1	260	380	1100	1500	QJF1038X1	11.4				
190	290	46	2.1	260	380	1100	1500	QJF1038	11.5				
190	340	55	4	439	702	1000	1400	QJF238	24.5	QA190	QA190		
200	280	51	2.1	210	420	1100	1500	QJF2940X2	10.3				
200	289.5	58	2.1	235	415	1100	1500	QJF3940X3	13.6				
200	310	51	2.1	305	475	1000	1400	QJF1040	15.2				
200	360	58	4	456	765	970	1350	QJF240	28.5	QA200	QA200		
220	300	60	2.1	160	340	1000	1400	QJF3944	12.5				
220	309.5	60	2.1	215	430	1000	1400	QJF3944X1	14.8				
220	340	56	3	450	620	970	1350	QJF1044	19.5				
240	329.5	60	2.1	230	480	970	1350	QJF3948X1	16.1				
240	340	60	2.1	270	580	950	1300	QJF3948X2	17.8				
240	360	56	3	460	655	950	1300	QJF1048	22.3				
260	359.5	65	2.1	280	630	920	1270	QJF2952X2	22.2				
260	369.5	60	2.1	300	660	900	1250	QJF2952X1	23				
260	374.5	60	2.1	300	660	900	1250	QJF2952X3	23.5				
260	400	65	4	510	765	850	1200	QJF1052	32.6				
280	375	65	2.1	235	525	850	1200	QJF2956X2	21				
280	389.5	65	2.1	300	700	820	1180	QJF2956X3	25.5				
280	420	65	4	540	835	800	1000	QJF1056	34.7				
300	420	65	3	355	870	800	1000	QJF2960X1	30.5				
300	460	74	4	630	1040	700	950	QJF1060	47				
320	440	65	3	360	900	700	950	QJF2964X2	31				
320	480	74	4	650	1090	650	850	QJF1064	49.5				
320	479.5	74	4	650	1090	650	850	QJF1064X1	50				
340	519.5	82	5	730	1380	620	820	QJF1068X1	66				
340	520	82	5	730	1380	620	820	QJF1068	66				