

Designations	Dimensions					Basic load ratings		Speed ratings		Installation dimensions			Weight
轴承代号	基本尺寸					基本额定载荷		极限转速		安装相关尺寸			重量
	d	D	B	r1min	r2min	Cr	C0r	脂润滑	油润滑	dhmax	Dsmin	Rmax	
	mm					KN		rpm		mm			Kg
7305C	25	62	17	1.1	0.6	28.6	16	10000	15000	32	55	1	0.224
7305BM	25	62	17	1.1	0.6	24.7	14	9000	13000	32	55	1	0.277
7306C	30	72	19	1.1	0.6	31.8	21	9000	13000	37	65	1	0.346
7306ACM	30	72	19	1.1	0.6	31	19.5	8000	11000	37	65	1	0.413
7306BM	30	72	19	1.1	0.6	33.6	18	8000	11000	37	65	1	0.371
7207C	35	72	17	1.1	0.6	32.5	22	9000	12000	42	65	1	0.304
7207BM	35	72	17	1.1	0.6	29	18	8000	11000	42	65	1	0.328
7307C	35	80	21	1.5	0.6	40.3	26	8000	11000	44	71	1.5	0.335
7307ACM	35	80	21	1.5	0.6	39	25	7800	1050	44	71	1.5	58.5
7307BM	35	80	21	1.5	0.6	39	25	7500	10000	44	71	1.5	0.551
7307B	35	80	21	1.5	0.6	39	25	6000	8000	44	71	1.5	0.481
7407ACM	35	100	25	1.5	0.6	70.2	42	6300	8500	44	91	1.5	1.14
7208C B7208C	40	80	18	1.1	0.6	36.4	25	8000	11000	47	73	1	0.364
7208CTN1/HQ1	40	80	18	1.1	0.6	36.4	25	6400	8800	47	73	1	0.383
7308C	40	80	18	1.1	0.6	47.2	21.5	10000	15000	47	73	1	0.312
7308ACM	40	90	23	1.5	0.6	46.8	32.5	7600	10000	49	81	1.5	0.624
7308B	40	90	23	1.5	0.6	46.8	31	6000	8000	49	81	1.5	0.711
7308BM	40	90	23	1.5	0.6	46.8	30	5100	6800	49	81	1.5	0.653
7408BM	40	90	23	1.5	0.6	46.8	30	6300	8500	49	81	1.5	0.711
7209C	45	85	19	1.1	0.6	40.3	29	9600	13600	52	78	1	0.418
7309C	45	85	19	1.1	0.6	40.3	29	12000	17000	52	78	1	0.403
7309ACM	45	100	25	1.5	0.6	63.7	42.5	7000	9500	64	91	1.5	0.834
7309BM	45	100	25	1.5	0.6	65	45	6000	8000	64	91	1.5	1.02
7010CM	50	80	16	1	0.3	26.5	17.3	8000	10000	57	73	1	0.309
7010ACM	50	80	16	1	0.3	25	20.5	7000	9000	57	73	1	0.314
7210C	50	90	20	1.1	0.6	42.9	32	7600	10000	57	83	1	0.458
B7210C	50	90	20	1.1	0.6	42.9	32	6080	8000	57	83	1	0.506
7210AC	50	90	20	1.1	0.6	40.3	30	5800	7800	57	83	1	0.46
7210B	50	90	20	1.1	0.6	37.7	29	4480	6400	57	83	1	0.487
7310ACM	50	110	27	2	1	71.5	49	5600	7500	60	100	2	1.16
7310BM	50	110	27	2	1	70	44	5000	6700	60	100	2	1.16
7310C	50	110	27	2	1	75.4	51	7000	8700	60	100	2	1.04
7310CM	50	110	27	2	1	75.4	51	7000	8700	60	100	2	1.16
7310B	50	110	27	2	1	70	44	4000	5400	60	100	2	1.05
7410ACM	50	130	31	2.1	1.1	105	70	5000	7000	62	118	2.1	2.3
7410BM	50	130	31	2.1	1.1	96.4	64	4000	6000	62	118	2.1	2.36
7011AC	55	90	18	1.1	0.6	31.2	26	10000	12000	62	83	1	0.385
7211C	55	100	21	1.5	0.6	53.3	40	8000	10000	64	91	1.5	0.599
7211AC	55	100	21	1.5	0.6	50.7	38	7100	10000	64	91	1.5	0.599
7211BM	55	100	21	1.5	0.6	34	34	5600	8000	65	91	1.5	1.698
7311C	55	120	29	2	1	92.3	65	7000	8700	65	110	2	1.44
7311AC	55	120	29	2	1	91	65	5000	6700	65	110	2	1.44
7311BM	55	120	29	2	1	81	56	4500	6300	65	110	2	1.61
7411ACM	55	140	33	2.1	1.1	121	84	4500	6300	67	128	2.1	2.79
7012AC	60	95	18	1.1	0.6	35.1	30	7100	10000	67	88	1	0.392
7212AC	60	110	22	1.5	0.6	55.9	43	6700	9000	69	101	1.5	0.786
7212C	60	110	22	1.5	0.6	58.5	45	9500	13000	69	101	1.5	0.786
7212BM	60	110	22	1.5	0.6	49.4	36	5600	7800	69	101	1.5	0.947
7312AC	60	130	31	2.1	1.1	94.9	67	4800	6300	72	118	2	1.8
7312BM	60	130	31	2.1	1.1	91	60	4300	5600	72	118	2	2.11
7412ACM	60	150	35	2.1	1.1	131	95	3800	5000	72	138	2	3.65
7412BM	60	150	35	2.1	1.1	120	86	3000	4000	72	138	2	3.42
7013AC	65	100	18	1.1	0.6	33.8	31	6700	9500	72	93	1	0.414
7213C	65	120	23	1.5	0.6	72.8	59	9000	12000	74	111	1.5	1.02
7213ACM	65	120	23	1.5	0.6	70.2	56	6000	8500	74	111	1.5	1.16
7313CM	65	140	33	2.1	1.1	120	88	8000	10000	77	128	2	2.6
7313ACM	65	140	33	2.1	1.1	114	84	4300	6000	77	128	2	2.61
7313BM	65	140	33	2.1	1.1	101	75	3800	5300	77	128	2	2.48
7413BM	65	160	37	2.1	1.1	129	97	2800	4300	77	148	2	3.82
7014ACM	70	110	20	1.1	0.6	44.2	41	6300	8500	77	103	1	0.725
7214CM	70	125	24	1.5	0.6	79.3	65	8500	11000	79	116	1.5	1.26
7214ACM	70	125	24	1.5	0.6	75.4	62	5600	8000	79	116	1.5	1.26
7214BM	70	125	24	1.5	0.6	68	54	4000	5600	79	116	1.5	1.27
7314C	70	150	35	2.1	1.1	134	100	6500	8000	82	138	2	2.69
7314AC	70	150	35	2.1	1.1	129	96	4000	5300	82	138	2	2.69
7314B	70	150	35	2.1	1.1	114	86	3200	4200	82	138	2	2.85
7414ACM	70	180	42	3	1.1	164	131	3600	5000	84	166	2.5	5.22
7414BM	70	180	42	3	1.1	148	118	2500	3500	84	166	2.5	5.64
7215C/P5	75	130	25	1.5	0.6	78.7	66.5	6800	8500	84	121	1.5	1.24
7215AC	75	130	25	1.5	0.6	79.3	67	5600	7500	84	121	1.5	1.18
7315CM	75	160	37	2.1	1.1	146	113	5800	7000	87	148	2	3.57
7315AC	75	160	37	2.1	1.1	140	109	3800	5000	87	148	2	3.11
7315B	75	160	37	2.1	1.1	125	97	3400	4800	87	148	2	3.7

7315ACJ	75	160	37	2.1	1.1	140	109	3400	4800	87	148	2	3.1
7415BM	75	190	45	3	1.1	159	130	2400	3800	89	176	2.5	6.8
7016ACM	80	125	22	1.1	0.6	55.9	53	5600	7500	87	118	1	0.983
7216CM	80	140	26	2	1	97.5	83	7500	10000	90	130	2	1.74
7216ACM	80	140	26	2	1	92.3	79	5000	7100	90	130	2	1.73
7216AC	80	140	26	2	1	92.3	79	5000	7100	90	130	2	1.48
7316AC	80	170	39	2.1	1.1	152	122	3600	4800	92	158	2	3.59
7316BM	80	170	39	2.1	1.1	135	109	3400	4500	92	158	2	4.25
7416AC	80	200	48	3	1.1	195	168	2600	3800	94	186	2.5	7.18
7416BM	80	200	48	3	1.1	178	153	2200	3200	96	184	2.5	8.05
7017ACM	85	130	22	1.1	0.6	57.2	56	5300	7100	92	123	1	1.12
7217CM	85	150	28	2	1	104	90	6700	9500	95	140	2	1.72
7217AC	85	150	28	2	1	98.8	86	4800	6700	95	140	2	1.91
7217BM	85	150	28	2	1	85.8	75	3600	4800	95	140	2	2.23
7317ACM	85	180	41	3	1.1	164	137	3400	4500	99	166	2.5	4.99
7317BM	85	180	41	3	1.1	146	122	3000	4000	99	166	2.5	4.98
7018ACM	90	140	24	1.5	0.6	67.6	66	4800	6700	99	131	1.5	1.39
7018BM	90	140	24	1.5	0.6	58.5	57	4300	6200	99	131	1.5	1.43
7218CM	90	160	30	2	1	122	105	6300	9000	100	150	2	2.47
7218ACM	90	160	30	2	1	117	100	4500	6000	100	150	2	2.35
7218BM	90	160	30	2	1	103	88	3200	4300	100	150	2	3.38
7318CM	90	190	43	3	1.1	183	158	5200	6300	104	176	2.5	5.79
7318ACM	90	190	43	3	1.1	176	152	3200	4300	104	176	2.5	6.18
7318BM	90	190	43	3	1.1	156	135	2800	3800	104	176	2.5	5.26
7418ACM	90	225	54	4	1.5	233	214	2900	4000	108	207	3	11.5
7418BM	90	225	54	4	1.5	210	193	1900	2900	110	205	3	11.4
7019ACM	95	145	24	1.5	0.6	53.5	69	5200	6300	93	135	1.5	1.44
7219CM	95	170	32	2.1	1.1	139	120	6000	8500	107	158	2	3.2
7219ACM	95	170	32	2.1	1.1	133	114	4300	5600	107	158	2	2.97
7219B	95	170	32	2.1	1.1	116	101	3000	4000	107	158	2	3
7319CM	95	200	45	3	1.1	196	174	5000	6000	109	186	2.5	6.67
7319ACM	95	200	45	3	1.1	189	167	3000	4000	109	186	2.5	6.67
7319BM	95	200	45	3	1.1	168	150	2900	3900	109	186	2.5	6.67
7020AC	100	150	24	1.5	0.6	76.7	77	4500	6000	109	141	1.5	1.25
7220CM	100	180	34	2.1	1.1	156	136	5600	8000	112	168	2	3.71
7220ACM	100	180	34	2.1	1.1	148	130	4000	5300	112	168	2	3.74
7220BM	100	180	34	2.1	1.1	130	114	2800	3800	112	168	2	4
7320ACM	100	215	47	3	1.1	213	199	2800	3800	114	201	2.5	9.61
7320BM	100	215	47	3	1.1	190	177	2400	3400	114	201	2.5	8.41