

Designations	Dimensions							Speed ratings		Basic load ratings		Installation dimensions		Weight
轴承代号	基本尺寸							极限转速		基本额定载荷		安装相关尺寸		
	d	D	T	B	C	r1min	r2min	润滑脂	润滑油	Cr	C0r	d1	D1	重量
	mm			mm				KN		rpm		mm		Kg
32220	100	180	49	46	39	3	2.5	345	490	1800	2600	137	148.184	5.31
33220	100	180	63	63	48	3	2.5	430	655	1700	2400	139.4	145.949	6.58
32320	100	215	77.5	73	60	4	3	610	840	1600	2200	153	171.65	13.2
32022	110	170	38	38	29	2.5	2	231	365	1800	2600	141.8	146.29	3.03
33022	110	170	47	47	37	2.5	2	300	465	1800	2600	139	146.265	3.75
32222	110	200	56	53	46	3	2.5	465	695	1700	2400	152	164.022	7.62
32322	110	240	84.5	80	65	4	3	735	1030	1400	1900	171	192.071	17.9
32024	120	180	38	38	29	2.5	2	237	395	1700	2400	150.8	155.239	3.31
33024	120	180	48	48	38	2.5	2	295	530	1800	2600	148	154.777	4.07
30224	120	215	43.5	40	34	3	2.5	330	445	1600	2200	163	181.257	6.32
32224	120	215	61.5	58	50	3	2.5	480	720	1600	2200	165	174.825	9.6
32324	120	260	90.5	86	69	4	3	845	1190	1300	1800	184	207.039	22.4
32026	130	200	45	45	34	2.5	2	340	580	1600	2200	165.82	172.043	5.06
32226	130	230	67.75	64	54	4	3	555	845	1500	2000	177	187.088	11.8
32326/YA6	130	280	99.5	93	78	3.7	3.7	870	1250	1100	1600	203.9	222.49	26.4
32028	140	210	45	45	34	2.5	2	330	560	1600	2200	175.9	180.72	5.84
32228	140	250	71.75	68	58	4	3	650	1000	1400	1900	192	204.046	14.7
32328	140	300	107.75	102	85	5	4	1090	1630	1200	1700	216	233	35.8
32230	150	270	77	73	60	4	3	1200	1700	735	1140	206	219.157	18.4
32232	160	290	84	80	67	4	3	1100	1600	925	1490	222	234.942	23.3
32334/YA6	170	360	127	120	100	3.7	3.7	950	1400	1300	2120	260	282.916	63.5
32334/YA6-	170	360	127	120	100	5	5	950	1400	1440	2140	260	282.916	63.5
32036	180	280	64	64	48	3	2.5	610	1070	950	1400	231	239.898	13.9
32236	180	320	91	86	71	5	4	1020	1670	950	1400	248	259.938	32.3
30238	190	340	60	55	46	5	4	950	1400	675	1040	257	219.083	20.6
32238	190	340	97	92	75	5	4	950	1300	1000	1080	263	279.024	36.1
32240	200	360	104	98	82	5	4	900	1300	1290	2250	273	294.88	42.6
32040	200	310	70	70	53	3	2.5	950	1400	760	1370	256	266.039	19.5
32044	220	340	76	76	57	4	3	900	1300	850	1520	279	292.464	23.9
32244	220	400	114	108	90	5	4	900	1300	1650	2770	308	326.455	62.7
30248	240	440	79	72	60	5	4	750	1000	1070	1550	330	370	46.8
32348	240	500	165	155	132	6	5	750	1000	2360	4100	358.2	394	146
32056	280	420	87	87	65	5	4	750	1000	1200	2300	349	361.811	40.4
32060	300	460	100	100	74	5	4	670	900	1460	2740	381.5	395.676	56.6
32064	320	480	100	100	74	5	4	1540	2940	630	850	400	415.64	62.7
32968	340	460	76	76	57	4	3	1000	2350	500	830	402	412.043	36.5
31068X2	340	520	86	82	64	5	4	1200	2050	500	630	415	457.896	73.9
32972	360	480	76	76	57	4	4	970	2220	500	630	426	430.612	38.5
30680	400	500	60	57	47	4	3	460	950	400	500	452	458.097	25.1
32980	400	540	87	82	71	5	4	1280	2880	380	480	470	482	54.1
T3GB420	420	620	95	90	67	5	5	600	800	1420	2940	512.7	547.12	88.3
30692	460	860	210	190	160	7.5	7.5	5590	10100	350	470	533	540	512
30696	480	950	240	225	174	9.5	9.5	6980	12500	310	420	708	751	761
T2GB500	500	720	110	100	82	6	6	2090	4100	360	450	596	644.741	128
306/510/HCC9DF	510	880	350	175	121	7.5	7.5	350	450	8400	17600	596	740	914