

Designations	外形尺寸 Boundary Dimension			安装尺寸 Bolt Hole Diameter		齿轮参数 Gear parameters		可允许的切线力 Permissible Tangential		重量 Weight
型号	Da	Di	H	La	Li	m	z	normal	maximum	(Kg)
162.16.0400.890.11.1503	475	304	55	448	352	4	77	11.5	23	31
162.16.0450.890.11.1503	531	345	55	500	400	5	70	14.4	28.8	40
162.16.0560.890.11.1503	641	455	55	610	510	5	92	14.4	28.8	49
162.16.0630.890.11.1503	717	516	55	682	578	6	87	17.3	34.6	59
162.20.0450.890.11.1503	536	336	62	505	395	6	57	19.9	39.8	48
162.20.0560.890.11.1503	646	444	62	615	505	6	75	19.9	39.8	60
162.20.0630.890.11.1503	722	496	62	687	573	8	63	26.6	53.2	75
162.20.0710.890.11.1503	802	576	62	767	653	8	73	26.6	53.2	84
162.25.0764.890.11.1503	866	636	73	830	698	6	107	24.1	48.2	113
162.25.0886.890.11.1503	988	744	73	952	820	8	94	32.1	64.2	138
162.25.0980.890.11.1503	1082	840	73	1046	914	8	106	32.1	64.2	152
162.25.1077.890.11.1503	1179	920	73	1143	1011	10	93	40.1	80.2	177
162.25.1120.890.11.1503	1232	960	73	1188	1052	10	97	40.1	80.2	192
162.25.1180.890.11.1503	1292	1020	73	1248	1112	10	103	40.1	80.2	202
162.25.1250.890.11.1503	1362	1090	73	1318	1182	10	110	40.1	80.2	213
162.25.1320.890.11.1503	1432	1140	73	1388	1252	12	96	48.2	96.4	240
162.28.1400.890.11.1503	1534	1200	80	1482	1318	12	101	53.5	107	330
162.28.1500.890.11.1503	1634	1308	80	1582	1418	12	110	53.5	107	343
162.28.1600.890.11.1503	1734	1386	80	1682	1518	14	100	62.4	124.8	391
162.28.1700.890.11.1503	1834	1498	80	1782	1618	14	108	62.4	124.8	398
162.36.1700.890.11.1503	1871	1456	100	1805	1595	14	105	79.1	158.2	636
162.36.1800.890.11.1503	1971	1554	100	1905	1695	14	112	79.1	158.2	675
162.36.1900.890.11.1503	2071	1652	100	2005	1795	14	119	79.1	158.2	720
162.36.2000.890.11.1503	2171	1764	100	2105	1895	14	127	79.1	158.2	731
162.40.2000.890.11.1503	2176	1744	108	2110	1890	16	138	98.4	196.8	832
162.40.2128.890.11.1503	2304	1872	108	2238	2018	16	146	98.4	196.8	882
162.40.2240.890.11.1503	2416	1984	108	2350	2130	16	153	98.4	196.8	932
162.40.2368.890.11.1503	2544	2112	108	2478	2258	16	161	98.4	196.8	980
162.45.2240.890.11.1503	2423	1962	119	2357	2123	18	110	123.2	246.4	1100
162.45.2366.890.11.1503	2549	2088	119	2483	2249	18	117	123.2	246.4	1160
162.45.2510.890.11.1503	2693	2232	119	2627	2393	18	125	123.2	246.4	1231
162.45.2654.890.11.1503	2837	2376	119	2771	2537	18	133	123.2	246.4	1302