

型号	主要数据尺寸			基本负荷额定值		疲劳负荷限值	额定速度		重量
Bearing Designation	Dimension(mm)			Basic load rating			Speed ratings(rpm)		Weight
				动态	静态		参照速度	限制速度	
	d	D	B	C	C0		Pu	Speed Ratings	
	mm			kN		kN	r/min		kg
305	25	62	17	22.9	15.6	0.67	20000	13000	0.24
306	30	72	19	29.2	20.8	0.88	18000	11000	0.37
307	35	80	21	39.1	28.5	1.2	16000	10000	0.48
308	40	90	23	46.8	36	1.53	14000	9000	0.64
309	45	100	25	59.4	46.5	1.96	13000	8000	0.88
310	50	110	27	64.4	52	2.2	11000	7000	1.15
311	55	120	29	79.2	67	2.85	10000	6700	1.5
312 NR	60	130	31	91.3	78	3.35	9500	6000	1.85
312-2ZNR	60	130	31	91.3	78	3.35	9500	4800	1.85
312-ZNR	60	130	31	91.3	78	3.35	9500	6000	1.85
313 NR	65	140	33	102	90	3.75	9000	5600	2.3
313-2ZNR	65	140	33	102	90	3.75	9000	4500	2.3
313-ZNR	65	140	33	102	90	3.75	9000	5600	2.3
314 NR	70	150	35	114	102	4.15	8000	5000	2.75
314-2ZNR	70	150	35	114	102	4.15	8000	4000	2.75
314-ZNR	70	150	35	114	102	4.15	8000	5000	2.75
305 NR	25	62	17	22.9	15.6	0.67	20000	13000	0.24
305-2ZNR	25	62	17	22.9	15.6	0.67	20000	10000	0.24
305-ZNR	25	62	17	22.9	15.6	0.67	20000	13000	0.24
306 NR	30	72	19	29.2	20.8	0.88	18000	11000	0.37
306-2ZNR	30	72	19	29.2	20.8	0.88	18000	9000	0.37
306-ZNR	30	72	19	29.2	20.8	0.88	18000	11000	0.37
307 NR	35	80	21	39.1	28.5	1.2	16000	10000	0.48
307-2ZNR	35	80	21	39.1	28.5	1.2	16000	8000	0.48
307-ZNR	35	80	21	39.1	28.5	1.2	16000	10000	0.48
308 NR	40	90	23	46.8	36	1.53	14000	9000	0.64
308-2ZNR	40	90	23	46.8	36	1.53	14000	7000	0.64
308-ZNR	40	90	23	46.8	36	1.53	14000	9000	0.64
309 NR	45	100	25	59.4	46.5	1.96	13000	8000	0.88
309-2ZNR	45	100	25	59.4	46.5	1.96	13000	6300	0.88
309-ZNR	45	100	25	59.4	46.5	1.96	13000	8000	0.88
310 NR	50	110	27	64.4	52	2.2	11000	7000	1.15
310-2ZNR	50	110	27	64.4	52	2.2	11000	5600	1.15
310-ZNR	50	110	27	64.4	52	2.2	11000	7000	1.15
311 NR	55	120	29	79.2	67	2.85	10000	6700	1.5
311-2ZNR	55	120	29	79.2	67	2.85	10000	5300	1.5
311-ZNR	55	120	29	79.2	67	2.85	10000	6700	1.5
305-Z	25	62	17	22.9	15.6	0.67	20000	10000	0.24
305-Z	25	62	17	22.9	15.6	0.67	20000	13000	0.24
306-Z	30	72	19	29.2	20.8	0.88	18000	9000	0.37
306-Z	30	72	19	29.2	20.8	0.88	18000	11000	0.37
307-Z	35	80	21	39.1	28.5	1.2	16000	8000	0.48
307-Z	35	80	21	39.1	28.5	1.2	16000	10000	0.48
308-Z	40	90	23	46.8	36	1.53	14000	7000	0.64
308-Z	40	90	23	46.8	36	1.53	14000	9000	0.64
309-Z	45	100	25	59.4	46.5	1.96	13000	6300	0.88
309-Z	45	100	25	59.4	46.5	1.96	13000	8000	0.88
310-Z	50	110	27	64.4	52	2.2	11000	5600	1.15
310-Z	50	110	27	64.4	52	2.2	11000	7000	1.15
311-Z	55	120	29	79.2	67	2.85	10000	5300	1.5
311-Z	55	120	29	79.2	67	2.85	10000	6700	1.5