

型号	主要数据尺寸			基本负荷额定值		疲劳负荷限值	额定速度		重量
Bearing Designation	Dimension(mm)			Basic load rating			Speed ratings(rpm)		Weight
				动态	静态		参照速度	限制速度	
	d	D	B	C	C0		Pu	Speed Ratings	
	mm			kN		kN	r/min		kg
6003 *	17	35	10	6.37	3.25	0.137	45000	28000	0.039
6003-2RSH	17	35	10	6.37	3.25	0.137	-	13000	0.039
6003-2RSL *	17	35	10	6.37	3.25	0.137	45000	22000	0.039
6003-2Z *	17	35	10	6.37	3.25	0.137	45000	22000	0.039
6003-RSH *	17	35	10	6.37	3.25	0.137	-	13000	0.039
6003-RSL *	17	35	10	6.37	3.25	0.137	45000	28000	0.039
6003-Z *	17	35	10	6.37	3.25	0.137	45000	28000	0.039
6004 *	20	42	12	9.95	5	0.212	38000	24000	0.069
6004-2RSH *	20	42	12	9.95	5	0.212	-	11000	0.069
6004-2RSL *	20	42	12	9.95	5	0.212	38000	19000	0.069
6004-2Z *	20	42	12	9.95	5	0.212	38000	19000	0.069
6004-RSH *	20	42	12	9.95	5	0.212	-	11000	0.069
6004-RSL *	20	42	12	9.95	5	0.212	38000	24000	0.069
6004-Z *	20	42	12	9.95	5	0.212	38000	24000	0.069
6001 *	12	28	8	5.4	2.36	0.1	60000	38000	0.022
6001-2RSH *	12	28	8	5.4	2.36	0.1	-	17000	0.022
6001-2RSL *	12	28	8	5.4	2.36	0.1	60000	30000	0.022
6001-2Z *	12	28	8	5.4	2.36	0.1	60000	30000	0.022
6001-RSH *	12	28	8	5.4	2.36	0.1	-	17000	0.022
6001-RSL *	12	28	8	5.4	2.36	0.1	60000	38000	0.022
6001-Z *	12	28	8	5.4	2.36	0.1	60000	38000	0.022
6002 *	15	32	9	5.85	2.85	0.12	50000	32000	0.03
6002-2RSH *	15	32	9	5.85	2.85	0.12	-	14000	0.03
6002-2RSL *	15	32	9	5.85	2.85	0.12	50000	26000	0.03
6002-2Z *	15	32	9	5.85	2.85	0.12	50000	26000	0.03
6002-RSH *	15	32	9	5.85	2.85	0.12	-	14000	0.03
6002-RSL *	15	32	9	5.85	2.85	0.12	50000	32000	0.03
6002-Z *	15	32	9	5.85	2.85	0.12	50000	32000	0.03
6008-2Z/VA208	40	68	15	11.6		160		256	0.17
6011-2Z/VA201	55	90	18	21.2		220		360	0.38
6020-2Z/VA208	100	150	24	54		300		480	1.1
6024-2Z/VA208	120	180	28	80		360		560	1.9
6003/VA201	17	35	10	3.25		100		180	0.039
6004-2Z/VA208	20	42	12	5		112		192	0.068
6005-2Z/VA201	25	47	12	6.55		112		212	0.08
6005-2Z/VA208	25	47	12	6.55		120		212	0.08
6005/VA201	25	47	12	6.55		120		212	0.08
6006-2Z/VA208	30	55	13	8.3		120		212	0.11
6203 *	17	40	12	9.95	4.75	0.2	38000	24000	0.065
6203 ETN9	17	40	12	11.4	5.4	0.228	38000	24000	0.064
6203-2RSH *	17	40	12	9.95	4.75	0.2	-	12000	0.065
6203-2RSL *	17	40	12	9.95	4.75	0.2	38000	19000	0.065
6203-2Z *	17	40	12	9.95	4.75	0.2	38000	19000	0.065
6203-RSH *	17	40	12	9.95	4.75	0.2	-	12000	0.065
6203-RSL *	17	40	12	9.95	4.75	0.2	38000	24000	0.065
6203-Z *	17	40	12	9.95	4.75	0.2	38000	24000	0.065
6204 *	20	47	14	13.5	6.55	0.28	32000	20000	0.11
6204 ETN9	20	47	14	15.6	7.65	0.325	32000	20000	0.096
6204-2RSH *	20	47	14	13.5	6.55	0.28	-	10000	0.11
6204-2RSL *	20	47	14	13.5	6.55	0.28	32000	17000	0.11
6204-2Z *	20	47	14	13.5	6.55	0.28	32000	17000	0.11
6204-RSH *	20	47	14	13.5	6.55	0.28	-	10000	0.11
6204-RSL *	20	47	14	13.5	6.55	0.28	32000	20000	0.11
6204-Z *	20	47	14	13.5	6.55	0.28	32000	20000	0.11
6201 *	12	32	10	7.28	3.1	0.132	50000	32000	0.037
6201-2RSH *	12	32	10	7.28	3.1	0.132	-	15000	0.037
6201-2RSL *	12	32	10	7.28	3.1	0.132	50000	26000	0.037
6201-2Z *	12	32	10	7.28	3.1	0.132	50000	26000	0.037
6201-RSH *	12	32	10	7.28	3.1	0.132	-	15000	0.037
6201-RSL *	12	32	10	7.28	3.1	0.132	50000	32000	0.037
6201-Z *	12	32	10	7.28	3.1	0.132	50000	32000	0.037
6202 *	15	35	11	8.06	3.75	0.16	43000	28000	0.045
6202-2RSH *	15	35	11	8.06	3.75	0.16	-	13000	0.045
6202-2RSL *	15	35	11	8.06	3.75	0.16	43000	22000	0.045
6202-2Z *	15	35	11	8.06	3.75	0.16	43000	22000	0.045
6202-RSH *	15	35	11	8.06	3.75	0.16	-	13000	0.045
6202-RSL *	15	35	11	8.06	3.75	0.16	43000	28000	0.045
6202-Z *	15	35	11	8.06	3.75	0.16	43000	28000	0.045
6207-2Z/VA201	35	72	17	15.3		160		256	0.29
6207-2Z/VA208	35	72	17	15.3		160		256	0.28
6207-2Z/VA228	35	72	17	15.3		160		256	0.28
6207/VA201	35	72	17	15.3		160		256	0.29
6208-2Z/VA201	40	80	18	19		160		256	0.37
6208-2Z/VA208	40	80	18	19		160		256	0.35
6208-2Z/VA228	40	80	18	19		160		256	0.35
6208/VA201	40	80	18	19		160		256	0.37
6209-2Z/VA201	45	85	19	21.6		180		292	0.41
6209-2Z/VA208	45	85	19	21.6		180		292	0.39
6209-2Z/VA228	45	85	19	21.6		180		292	0.39
6209/VA201	45	85	19	21.6		180		292	0.41
6210-2Z/VA201	50	90	20	23.2		180		292	0.46

6210-2Z/VA208	50	90	20	23.2		180		292	0.45
6210-2Z/VA228	50	90	20	23.2		180		292	0.45
6210/VA201	50	90	20	23.2		180		292	0.46
6211-2Z/VA201	55	100	21	29		220		360	0.61
6211-2Z/VA208	55	100	21	29		220		360	0.59
6211-2Z/VA228	55	100	21	29		220		360	0.59
6211/VA201	55	100	21	29		220		360	0.61
6212-2Z/VA201	60	110	22	36		220		360	0.78
6212-2Z/VA208	60	110	22	36		220		360	0.74
6212-2Z/VA228	60	110	22	36		220		360	0.74
6212/VA201	60	110	22	36		220		360	0.78
6213-2Z/VA208	65	120	23	40.5		220		360	0.94
6213-2Z/VA228	65	120	23	40.5		220		360	0.94
6213/VA201	65	120	23	40.5		220		360	0.99
6214-2Z/VA208	70	125	24	45		260		420	1
6214/VA201	70	125	24	45		260		420	1.05
6215-2Z/VA201	75	130	25	49		260		420	1.2
6215-2Z/VA208	75	130	25	49		260		420	1.15
6215-2Z/VA228	75	130	25	49		260		420	1.15
6215/VA201	75	130	25	49		260		420	1.2
6216-2Z/VA208	80	140	26	55		260		420	1.35
6217-2Z/VA208	85	150	28	64		300		480	1.7
6217/VA201	85	150	28	64		300		480	1.8
6218-2Z/VA228	90	160	30	73.5		300		480	2.15
6219-2Z/VA201	95	170	32	81.5		300		480	2.6
6219-2Z/VA228	95	170	32	81.5		300		480	2.45
6219/VA201	95	170	32	81.5		300		480	2.6
6220/VA201	100	180	34	93		300		480	3.15
6201-2Z/VA201	12	32	10	3.1		100		180	0.037
6201-2Z/VA228	12	32	10	3.1		100		180	0.037
6201/VA201	12	32	10	3.1		100		180	0.037
6202-2Z/VA201	15	35	11	3.75		100		180	0.045
6202-2Z/VA228	15	35	11	3.75		100		180	0.043
6202/VA201	15	35	11	3.75		100		180	0.045
6203-2Z/VA201	17	40	12	4.75		100		180	0.065
6203-2Z/VA228	17	40	12	4.75		100		180	0.06
6203/VA201	17	40	12	4.75		100		180	0.065
6204-2Z/VA201	20	47	14	6.55		112		192	0.11
6204-2Z/VA228	20	47	14	6.55		112		192	0.1
6204/VA201	20	47	14	6.55		112		192	0.11
6205-2Z/VA201	25	52	15	7.8		120		212	0.13
6205-2Z/VA228	25	52	15	7.8		120		212	0.12
6205/VA201	25	52	15	7.8		120		212	0.13
6206-2Z/VA201	30	62	16	11.2		120		212	0.2
6206-2Z/VA208	30	62	16	11.2		120		212	0.19
6206-2Z/VA228	30	62	16	11.2		120		212	0.19
6206/VA201	30	62	16	11.2		120		212	0.2
6302-RSH *	15	42	13	11.9	5.4	0.228	-	12000	0.082
6302-RSL *	15	42	13	11.9	5.4	0.228	38000	24000	0.082
6302-Z *	15	42	13	11.9	5.4	0.228	38000	24000	0.082
6303 *	17	47	14	14.3	6.55	0.275	34000	22000	0.12
6303-2RSH *	17	47	14	14.3	6.55	0.275	-	11000	0.12
6303-2RSL *	17	47	14	14.3	6.55	0.275	34000	17000	0.12
6303-2Z *	17	47	14	14.3	6.55	0.275	34000	17000	0.12
6303-RSH *	17	47	14	14.3	6.55	0.275	-	11000	0.12
6303-RSL *	17	47	14	14.3	6.55	0.275	34000	22000	0.12
6303-Z *	17	47	14	14.3	6.55	0.275	34000	22000	0.12
6304 *	20	52	15	16.8	7.8	0.335	30000	19000	0.14
6304 ETN9	20	52	15	18.2	9	0.38	30000	19000	0.14
6304-2RSH *	20	52	15	16.8	7.8	0.335	-	9500	0.14
6304-2RSL *	20	52	15	16.8	7.8	0.335	30000	15000	0.14
6304-2Z *	20	52	15	16.8	7.8	0.335	30000	15000	0.14
6304-RSH *	20	52	15	16.8	7.8	0.335	-	9500	0.14
6304-RSL *	20	52	15	16.8	7.8	0.335	30000	19000	0.14
6304-Z *	20	52	15	16.8	7.8	0.335	30000	19000	0.14
6301 *	12	37	12	10.1	4.15	0.176	45000	28000	0.06
6301-2RSH *	12	37	12	10.1	4.15	0.176	-	14000	0.06
6301-2RSL *	12	37	12	10.1	4.15	0.176	45000	22000	0.06
6301-2Z	12	37	12	10.1	4.15	0.176	45000	22000	0.06
6301-RSH *	12	37	12	10.1	4.15	0.176	-	14000	0.06
6301-RSL *	12	37	12	10.1	4.15	0.176	45000	28000	0.06
6301-Z	12	37	12	10.1	4.15	0.176	45000	28000	0.06
6302 *	15	42	13	11.9	5.4	0.228	38000	24000	0.082
6302-2RSH *	15	42	13	11.9	5.4	0.228	-	12000	0.082
6302-2RSL *	15	42	13	11.9	5.4	0.228	38000	19000	0.082
6302-2Z *	15	42	13	11.9	5.4	0.228	38000	19000	0.082
6307-2Z/VA208	35	80	21	19		160		256	0.44
6307/VA201	35	80	21	19		160		256	0.46
6308-2Z/VA201	40	90	23	24		160		256	0.63
6308-2Z/VA208	40	90	23	24		160		256	0.61
6308-2Z/VA228	40	90	23	24		160		256	0.61
6308/VA201	40	90	23	24		160		256	0.63
6309-2Z/VA208	45	100	25	31.5		180		292	0.79
6309/VA201	45	100	25	31.5		180		292	0.83
6310-2Z/VA201	50	110	27	38		180		292	1.05
6310-2Z/VA208	50	110	27	38		180		292	1.04
6310-2Z/VA228	50	110	27	38		180		292	1.04

6310/VA201	50	110	27	38		180		292	1.05
6311-2Z/VA208	55	120	29	45		220		360	1.33
6311/VA201	55	120	29	45		220		360	1.35
6312-2Z/VA208	60	130	31	52		220		360	1.6
6312/VA201	60	130	31	52		220		360	1.7
6313-2Z/VA208	65	140	33	60		220		360	2
6313/VA201	65	140	33	60		220		360	2.1
6314-2Z/VA208	70	150	35	68		260		420	2.7
6314/VA201	70	150	35	68		260		420	2.5
6315-2Z/VA208	75	160	37	76.5		260		420	3
6315/VA201	75	160	37	76.5		260		420	3
6316-2Z/VA208	80	170	39	86.5		260		420	3.55
6300-2Z/VA201	10	35	11	34		80		148	0.053
6304-2Z/VA201	20	52	15	7.8		112		192	0.13
6304-2Z/VA208	20	52	15	7.8		112		192	0.13
6304/VA201	20	52	15	7.8		112		192	0.13
6305-2Z/VA228	25	62	17	11.6		120		212	0.22
6305/VA201	25	62	17	11.6		120		212	0.23
6306-2Z/VA208	30	72	19	16		120		212	0.34
6306-2Z/VA228	30	72	19	16		120		212	0.34
6306/VA201	30	72	19	16		120		212	0.35
W6002	15	32	9	4.68	2.75	0.12	50000	32000	0.030
W6002 2RS1	15	32	9	4.68	2.75	0.12		14000	0.030
W6002 2Z	15	32	9	4.68	2.75	0.12	50000	26000	0.030
W6202	15	35	11	6.5	3.65	0.16	43000	28000	0.045
W6202 2RS1	15	35	11	6.5	3.65	0.16		13000	0.045
W6202 2Z	15	35	11	6.5	3.65	0.16	43000	22000	0.045
W6302	15	42	13	9.56	5.2	0.228	38000	24000	0.085
W6302 2RS1	15	42	13	9.56	5.2	0.228		12000	0.082
W6302 2Z	15	42	13	9.56	5.2	0.228	38000	19000	0.082
W6003	17	35	10	5.07	3.15	0.137	45000	28000	0.039
W6003 2RS1	17	35	10	5.07	3.15	0.137		13000	0.039
W6003 2Z	17	35	10	5.07	3.15	0.137	45000	22000	0.039
W6203	17	40	12	8.06	4.65	0.2	38000	24000	0.065
W6203 2RS1	17	40	12	8.06	4.65	0.2		12000	0.065
W6203 2Z	17	40	12	8.06	4.65	0.2	38000	19000	0.065
W6303	17	47	14	11.4	6.3	0.275	34000	22000	0.12
W6303 2RS1	17	47	14	11.4	6.3	0.275		11000	0.12
W6303 2Z	17	47	14	11.4	6.3	0.275	34000	17000	0.12
W6004	20	42	12	7.93	4.9	0.212	38000	24000	0.069
W6004 2RS1	20	42	12	7.93	4.9	0.212		11000	0.069
W6004 2Z	20	42	12	7.93	4.9	0.212	38000	19000	0.069
W6204	20	47	14	10.8	6.4	0.28	32000	20000	0.11
W6204 2RS1	20	47	14	10.8	6.4	0.28		10000	0.11
W6204 2Z	20	47	14	10.8	6.4	0.28	32000	17000	0.11
W6304	20	52	15	13.5	7.65	0.335	30000	19000	0.14
W6304 2RS1	20	52	15	13.5	7.65	0.335		9500	0.14
W6304 2Z	20	52	15	13.5	7.65	0.335	30000	15000	0.14
W6005	25	47	12	8.52	5.7	0.25	32000	20000	0.080
W6005 2RS1	25	47	12	8.52	5.7	0.25		9500	0.080
W6005 2Z	25	47	12	8.52	5.7	0.25	32000	16000	0.080
W6205	25	52	15	11.9	7.65	0.335	28000	18000	0.13
W6205 2RS1	25	52	15	11.9	7.65	0.335		8500	0.13
W6205 2Z	25	52	15	11.9	7.65	0.335	28000	14000	0.13
W6305	25	62	17	17.2	10.8	0.475	24000	16000	0.23
W6305 2RS1	25	62	17	17.2	10.8	0.475		7500	0.23
W6305 2Z	25	62	17	17.2	10.8	0.475	24000	13000	0.23
W6006	30	55	13	11.1	8	0.355	28000	17000	0.12
W6006 2RS1	30	55	13	11.1	8	0.355		8000	0.12
W6006 2Z	30	55	13	11.1	8	0.355	28000	14000	0.12
W6206	30	62	16	16.3	10.8	0.475	24000	15000	0.20
W6206 2RS1	30	62	16	16.3	10.8	0.475		7500	0.20
W6206 2Z	30	62	16	16.3	10.8	0.475	24000	12000	0.20
W6306	30	72	19	22.5	14.6	0.64	20000	13000	0.35
W6306 2RS1	30	72	19	22.5	14.6	0.64		6300	0.35
W6306 2Z	30	72	19	22.5	14.6	0.64	20000	11000	0.35
W6007	35	62	14	13.5	10	0.44	24000	15000	0.16
W6007 2RS1	35	62	14	13.5	10	0.44		7000	0.16
W6007 2Z	35	62	14	13.5	10	0.44	24000	12000	0.16
W6207	35	72	17	21.6	14.6	0.655	20000	13000	0.29
W6207 2RS1	35	72	17	21.6	14.6	0.655		6300	0.29
W6207 2Z	35	72	17	21.6	14.6	0.655	20000	10000	0.29
W6008	40	68	15	14	10.8	0.49	22000	14000	0.19
W6008 2RS1	40	68	15	14	10.8	0.49		6300	0.19
W6008 2Z	40	68	15	14	10.8	0.49	22000	11000	0.19
W6208	40	80	18	24.7	17.3	0.75	18000	11000	0.37
W6208 2RS1	40	80	18	24.7	17.3	0.75		5600	0.37
W6208 2Z	40	80	18	24.7	17.3	0.75	18000	9000	0.37
W6009	45	75	16	17.8	14.6	0.64	20000	12000	0.25
W6009 2RS1	45	75	16	17.8	14.6	0.64		5600	0.25
W6009 2Z	45	75	16	17.8	14.6	0.64	20000	10000	0.25
W6209	45	85	19	27.6	19.6	0.865	17000	11000	0.41
W6209 2RS1	45	85	19	27.6	19.6	0.865		5000	0.41
W6209 2Z	45	85	19	27.6	19.6	0.865	17000	8500	0.41
W6010	50	80	16	18.2	16	0.71	18000	11000	0.26
W6010 2RS1	50	80	16	18.2	16	0.71		5000	0.26
W6010 2Z	50	80	16	18.2	16	0.71	18000	9000	0.26

W6210	50	90	20	29,6	22,4	0,98	15000	10000	0,46
W6210 2RS1	50	90	20	29,6	22,4	0,98		4800	0,46
W6210 2Z	50	90	20	29,6	22,4	0,98	15000	8000	0,46
W 6000	10	26	8	3,9	1,9	0,083	67000	40000	0,019
W 6000 2RS1	10	26	8	3,9	1,9	0,083		19000	0,019
W 6000 2Z	10	26	8	3,9	1,9	0,083	67000	34000	0,019
W 6200	10	30	9	4,23	2,28	0,1	56000	34000	0,032
W 6200 2RS1	10	30	9	4,23	2,28	0,1		17000	0,032
W 6200 2Z	10	30	9	4,23	2,28	0,1	56000	28000	0,032
W 6300	10	35	11	6,76	3,25	0,143	50000	32000	0,053
W 6300 2RS1	10	35	11	6,76	3,25	0,143		15000	0,053
W 6300 2Z	10	35	11	6,76	3,25	0,143	50000	26000	0,053
W 6001	12	28	8	4,23	2,28	0,1	60000	38000	0,022
W 6001 2RS1	12	28	8	4,23	2,28	0,1		17000	0,022
W 6001 2Z	12	28	8	4,23	2,28	0,1	60000	30000	0,022
W 6201	12	32	10	5,85	3	0,132	50000	32000	0,037
W 6201 2RS1	12	32	10	5,85	3	0,132		15000	0,037
W 6201 2Z	12	32	10	5,85	3	0,132	50000	26000	0,037
W 6301	12	37	12	8,19	4,05	0,176	45000	28000	0,06
W 6301 2RS1	12	37	12	8,19	4,05	0,176		14000	0,060
W 6301 2Z	12	37	12	8,19	4,05	0,176	45000	22000	0,060