

型号	主要数据尺寸												额定速度		重量
Bearing Designation	Dimension(mm)												Speed ratings(rpm)		Weight
													参照速度	限制速度	
	d	D	B	C	H	dk	S	d1max	D1min	A	rs,r1smin	α=	Speed Ratings	Limiting Speed	
	mm												r/min		kg
GX100S	100	210	51	46	59	222	45	198	127	15	1.1	8	1300	6470	10.9
GX10S	10	30	7.5	7	9.5	32	7	27.5	15.5	3	0.6	9	27	136	0.036
GX120S	120	230	53.5	50	64	250	52.5	220	145	16.5	1.1	6	1530	7580	13.9
GX12S	12	35	9.5	9.3	13	38	8	32	18	4	0.6	8	37	188	0.072
GX140S	140	260	61	54	72	274	52.5	243	177	23	1.5	6	1820	9040	18.1
GX15S	15	42	11	10.8	15	46	10	39	22.5	5	0.6	8	53	267	0.108
GX160S	160	290	66	58	77	313	65	271	200	23	1.5	7	2100	10440	23.2
GX17S	17	47	11.8	11.2	16	52	11	43.5	27	5	0.6	10	61	311	0.137
GX180S	180	320	74	62	86	340	67.5	299	225	26	1.5	8	2430	12070	30.9
GX200S	200	340	80	66	87	365	70	320	247	27	1.5	8	3070	15280	34.2
GX20S	20	55	14.5	13.8	20	60	12.5	50	31	6	1	9	84	425	0.246
GX25S	25	62	16.5	16.7	22.5	68	14	58.5	34.5	6	1	7	134	672	0.415
GX30S	30	75	19	19	26	82	17.5	70	42	8	1	7	182	909	0.614
GX35S	35	90	22	20.7	28	98	22	84	50.5	8	1	8	266	1330	0.973
GX40S	40	105	27	21.5	32	114	24.5	97	59	9	1	9	357	1810	1.59
GX45S	45	120	31	25.5	36.5	128	27.5	110	67	11	1	9	486	2470	2.24
GX50S	50	130	33	30.5	42.5	139	30	120	70	10	1	7	554	2810	3.14
GX60S	60	150	37	34	45	160	35	140	84	12.5	1	8	748	3820	4.63
GX70S	70	160	42	36.5	50	176	35	153	94.5	13.5	1	8	902	4610	5.37
GX80S	80	180	43.5	38	50	197	42.5	172	107.5	14.5	1	8	1110	5700	6.91
GX10T	10	30	7.5	7	9.5	32	7	27.5	15.5		0.6	5	45	90	0.036
GX12T	12	35	9.5	9.3	13	38	8	32	18		0.6	5	65	130	0.072
GX15T	15	42	11	10.8	15	46	10	39	22.5		0.6	6	95	190	0.108
GX17T	17	47	11.8	11.2	16	52	11	43.5	27		0.6	4	110	220	0.137
GX20T	20	55	14.5	13.8	20	60	12.5	50	31		1	5	150	300	0.246
GX25T	25	62	16.5	16.7	22.5	68	14	58.5	34.5		1	5	245	490	0.415
GX30T	30	75	19	19	26	82	17.5	70	42		1	5	335	670	0.614
GX35T	35	90	22	20.7	28	98	22	84	50.5		1	5	490	980	0.973
GX40T	40	105	27	21.5	32	114	24.5	97	59		1	6	675	1350	1.59
GX45T	45	120	31	25.5	36.5	128	27.5	110	67		1	6	915	1830	2.24
GX50T	50	130	33	30.5	42.5	139	30	120	70		1	6	1040	2080	3.14
GX60T	60	150	37	34	45	160	35	140	84		1	6	1400	2800	4.63
GX70T	70	160	42	36.5	50	176	35	153	94.5		1	3	1590	3180	5.37
GX80T	80	180	43.5	38	50	197	42.5	172	107.5		1	4	1960	3920	6.91
GX100T	100	210	51	46	59	222	45	198	127		1.1	4	2270	4540	10.9
GX120T	120	230	53.5	50	64	250	52.5	220	145		1.1	3	2560	5120	13.9
GX140T	140	260	61	54	72	274	52.5	243	177		1.5	3	3050	6100	18.1
GX160T	160	290	66	58	77	313	65	271	200		1.5	2	3520	6250	23.2
GX180T	180	320	74	62	86	340	67.5	299	225		1.5	4	4070	7220	30.9
GX200T	200	340	80	66	87	365	70	320	247		1.5	1	4780	9150	34.2