

轴承型号		外形尺寸(mm)							重量
Designation		Dimensions							Weight
Cone	Cup	d	D	T	B	C	R	r	kg
368A	362A	50.8	88.9	20.638	22.225	16.513	3.5	1.3	0.516
387A	382A	57.15	96.838	21	21.946	15.875	3.5	0.8	0.581
387AS	382AS	57.15	96.838	21	21.946	15.875	5	0.8	0.576
395	394A	63.5	110	22	21.946	18.824	3.5	1.3	0.88
418	414	38.1	88.5	26.988	29.083	22.225	3.5	1.5	0.841
462	453X	57.15	104.775	30.16	29.317	24.605	2.3	3.3	1.04
482	472	69.85	120	29.794	29.007	24.237	3.5	2	1.3
484	472	70	120	29.794	29.007	24.237	2	2	1.3
528	522	47.625	101.6	34.925	36.068	26.988	3.5	3.3	1.3
567	563	73.025	127	36.512	36.17	28.575	3.5	3.3	1.81
580	572	82.55	139.992	36.512	36.098	28.575	3.5	3.3	2.22
665	653	85.275	146.05	41.275	41.275	31.75	3.5	3.3	4.79
677	672	85.725	168.275	41.275	41.275	30.162	3.5	3.3	4.18
749	742	85.026	150.089	44.45	46.672	35.512	3.5	3.3	3.17
2788	2720	38.1	70.2	23.812	25.654	19.05	3.5	3.3	0.492
3370	3820	34.925	80.167	29.37	30.391	23.812	3.5	3.3	0.742
3789	3720	50.8	93.264	30.162	30.302	23.812	3.5	3.3	0.868
3872	3820	34.925	85.725	60.162	30.162	23.812	3.5	3.3	0.88
3982	3920	63.5	112.712	30.162	30.048	23.812	3.5	3.3	1.17
3984	3920	66.675	112.712	30.162	30.048	23.812	3.5	3.3	1.1
4388	4335	41.275	90.488	39.688	40.386	33.338	3.5	3.3	1.22
7100	7196	25.4	50.005	13.495	14.26	9.525	1	1	0.119
11590	11520	15.875	42.862	14.288	14.288	9.525	1.5	1.5	0.1
14125A	14276	31.75	69.012	19.845	19.583	15.875	3.5	1.3	0.36
15101	15245	25.4	62	19.05	20.638	14.288	3.5	1.3	0.3
15103S	15243	26.126	61.912	19.05	19.939	14.288	0.8	2	0.28
15123	15245	31.75	62	18.161	19.05	14.288		1.3	0.244
18590	18520	41.275	73.025	16.667	17.462	12.7	3.5	1.5	0.275
18790	18720	50.8	85	17.462	17.462	13.495	3.5	1.5	0.374
24780	24720	41.275	76.2	22.225	23.02	17.462	3.5	0.8	0.474
25580	25520	44.45	82.931	23.812	25.4	19.05	3.5	0.8	0.561
25590	25520	45.618	82.931	23.812	25.4	19.05	3.5	0.8	0.544
25590	25523	45.618	82.931	26.988	25.4	22.225	3.5	2.3	0.603
25877	25821	34.925	73.025	23.812	24.608	19.05	1.5	0.8	0.471
26882	26822	41.275	79.375	23.812	25.4	19.05	3.5	0.3	0.53
28985	28920	60.325	101.6	25.4	25.4	19.845	3.5	3.3	0.801
29590	29520	66.675	107.95	25.4	25.4	19.05	3.5	3.3	0.844
33275	33462	69.85	117.474	30.162	30.162	23.812	3.5	3.3	1.25
39581	39520	57.15	112.712	30.162	30.162	23.812	8	3.3	1.38
JH211749	JM211710	65	120	39	38.5	32	3	2.5	1.874
R196Z-4				196.85	241.3	23.812	2.1		
CR4411				220	290	32.5	5.6		
CR6016				300	380	38	8.2		
T2ED045				45	95	36			
T2ED065				65	130	37.1			
HR322822C				22	80	19			
32205				25	52	18	0.186		
33205				25	52	22	0.216		
33207				35	72	28	0.515		