

型号	尺寸 (mm)							额定载荷 (KN)	
Bearing Designation	Dimension(mm)							Basic load rating	
								动态	静态
	d	D	D1	C	C1	B	θ	Cr	Cor
CG30R1-1	30	73	65	27	20.5	26	15 °	50	62
CG30R1-2	30	77	65	34	22	26	12 °	57.8	72.8
CG35R1-1	35	69	60	26	20	20	10 °	39.6	56.9
CG35R1-4	35	87	75	29	22	31	15 °	39.6	56.9
CG40R1-2	40	100	82	47	35	26	16 °	58.3	79.9
CG40R1-3	40	78	70	25	19	26.5	10 °	54.1	78.8
CG40R1-7	40	124	106	36	25	26	15.5 °	83.8	116.4
CG40R1-8	40	108	94	33.2	25	23	6 °	52.8	63.6
CG40R1-10	40	100	82	36	27	26	15 °	58.3	79.9
CG45R1-1	45	150	128	69	50	50.8	20 °	174	230
CG45R1-5	45	136	127	38	31	40	15 °	150.1	275.8
CG50R1-1	50	130	106	52	36	40	10 °	121	150.9
CG50R1-4	50	124	104	43	31	30	12 °	76.5	113.7
CG50R1-6	50	124	104	56	42	35	8.5 °	76.5	113.7
CG55R1-1	55	158	130	65	55	67	10 °	265.7	391.5
CG55R1-2	55	145	120	56	41	40	10 °	155	196
CG55R1-5	55	156	136	52	37	40	6 °	155	196
CG60R1-1	60	165	130	62.5	47	44.5	14 °	229	315