

轴承型号	外形尺寸				有关安装尺寸(mm)			重量	
Designation	Dimensions				Mounting dimensions			Weight	
	d	D	B	r min	da	da	Da	(kg)	
	(mm)				最小 min	最大 max	最大 max	ZrO2	Si3N4
126C	6	19	6	0.3	8	17	0.3	0.007	0.004
127C	7	22	7	0.3	9	20	0.3	0.011	0.006
108C	8	22	7	0.3	10	20	0.3	0.011	0.006
129C	9	26	8	0.6	13	22	0.6	0.017	0.009
1200C	10	30	9	0.6	14	26	0.6	0.026	0.014
2200C	10	30	14	0.6	14	26	0.6	0.036	0.019
1300C	10	25	11	0.6	14	31	0.6	0.045	0.024
2300C	10	25	17	0.6	14	31	0.6	0.065	0.035
1201C	12	32	10	0.6	16	28	0.6	0.031	0.016
2201C	12	32	14	0.6	16	28	0.6	0.041	0.022
1301C	12	37	12	1	17	32	1	0.052	0.027
2301C	12	37	17	1	17	32	1	0.073	0.039
1202C	15	35	11	0.6	19	31	0.6	0.038	0.02
2202C	15	35	14	0.6	19	31	0.6	0.046	0.025
1302C	15	42	13	1	20	37	1	0.072	0.039
2302C	15	42	17	1	20	37	1	0.088	0.047
1203C	17	40	12	0.6	21	36	0.6	0.056	0.03
2203C	17	40	16	0.6	21	36	0.6	0.068	0.036
1303C	17	47	14	1	22	42	1	0.1	0.053
2303C	17	47	19	1	22	42	1	0.12	0.065
1204C	20	47	14	1	25	42	1	0.09	0.049
2204C	20	47	18	1	25	42	1	0.11	0.057
1304C	20	52	15	1.1	26.5	45.5	1	0.13	0.067
1304C	20	52	21	1.1	26.5	45.5	1	0.16	0.086
1205C	25	52	15	1	30	47	1	0.11	0.058
2205C	25	52	18	1	30	47	1	0.13	0.067
1305C	25	62	17	1.1	31.5	55.5	1	0.2	0.11
2305C	25	62	24	1.1	31.5	55.5	1	0.26	0.14
1206C	30	62	16	1	35	57	1	0.17	0.09
2206C	30	62	20	1	35	57	1	0.2	0.11
1306C	30	72	19	1.1	36.5	65.5	1	0.3	0.16
2306C	30	72	27	1.1	36.5	65.5	1	0.38	0.21
1207C	35	72	17	1.1	41.5	65.5	1	0.25	0.13
2207C	35	72	23	1.1	41.5	65.5	1	0.31	0.17
1307C	35	80	21	1.5	43	72	1.5	0.39	0.21
2307C	35	80	31	1.5	43	72	1.5	0.52	0.28
1208C	40	80	18	1.1	46.5	73.5	1	0.32	0.17
2208C	40	80	23	1.1	46.5	73.5	1	0.39	0.21
1308C	40	90	23	1.5	48	82	1.5	0.55	0.29
2308C	40	90	33	1.5	48	82	1.5	0.71	0.38
1209C	45	85	19	1.1	51.5	78.5	1	0.36	0.19
2209C	45	85	23	1.1	51.5	78.5	1	0.42	0.22
1309C	45	100	25	1.5	53	92	1.5	0.74	0.39
2309C	45	100	36	1.5	53	92	1.5	0.95	0.5
1210C	50	90	20	1.1	56.5	83.5	1	0.4	0.22
2210C	50	90	23	1.1	56.5	83.5	1	0.45	0.24
1310C	50	110	27	2	59	101	2	0.93	0.5
2310C	50	110	40	2	59	101	2	1.26	0.67
1211C	55	100	21	1.5	63	92	1.5	0.54	0.29
2211C	55	100	25	1.5	63	92	1.5	0.62	0.33
1311C	55	120	29	2	64	111	2	1.22	0.65

2311C	55	120	43	2	64	111	2	1.62	0.86
1212C	60	110	22	1.5	68	102	1.5	0.69	0.37
2212C	60	110	28	1.5	68	102	1.5	0.84	0.45
1312C	60	130	31	2.1	71	119	2	1.51	0.8
2312C	60	130	46	2.1	71	119	2	2	1.07
1213C	65	120	23	1.5	73	112	1.5	0.88	0.47
2213C	65	120	31	1.5	73	112	1.5	1.12	0.6
1313C	65	140	33	2.1	76	129	2	1.88	1.01
2313C	65	140	48	2.1	76	129	2	2.48	1.33
1214C	70	125	24	1.5	78	117	1.5	0.97	0.52
2214C	70	125	31	1.5	78	117	1.5	1.17	0.62
1314C	70	150	35	2.1	81	139	2	2.3	1.23
2314C	70	150	51	2.1	81	139	2	3.25	1.74
1215C	75	130	25	1.5	83	122	1.5	1.05	0.56
2215C	75	130	31	1.5	83	122	1.5	1.25	0.66
1216C	80	140	26	2	89	131	2	1.28	0.69
2216C	80	140	33	2	89	131	2	1.55	0.82
1217C	85	150	28	2	94	141	2	1.59	0.85
2217C	85	150	36	2	94	141	2	1.94	1.03