

轴承型号 Designation	外形尺寸				有关安装尺寸(mm)		重量	
	Dimensions				Mounting dimensions		Weight	
	d	D	B	r min	d1	D1	(kg)	
	(mm)				最小 min	最大 max	ZrO2	Si3N4
SS51100	10	24	9	0.3	24	11	0.015	0.0078
SS51200	10	26	11	0.6	26	12	0.022	0.011
SS51101	12	26	9	0.3	26	13	0.016	0.009
SS51201	12	28	11	0.6	28	14	0.024	0.013
SS51102	15	28	9	0.3	28	16	0.018	0.0094
SS51202	15	32	12	0.6	32	17	0.033	0.018
SS51103	17	30	9	0.3	30	18	0.019	0.01
SS51203	17	35	12	0.6	35	19	0.038	0.021
SS51104	20	35	10	0.3	35	21	0.028	0.015
SS51204	20	40	14	0.6	40	22	0.059	0.032
SS51105	25	42	11	0.6	42	26	0.043	0.023
SS51205	25	47	15	0.6	47	27	0.085	0.046
SS51106	30	47	11	0.6	47	32	0.049	0.026
SS51206	30	52	16	0.6	52	32	0.11	0.056
SS51107	35	52	12	0.6	52	37	0.062	0.033
SS51207	35	62	18	1	62	37	0.16	0.086
SS51108	40	60	13	0.6	60	42	0.092	0.049
SS51208	40	68	19	1	68	42	0.21	0.11
SS51109	45	65	14	0.6	65	47	0.11	0.059
SS51209	45	73	20	1	73	47	0.24	0.13
SS51110	50	70	14	0.6	70	52	0.12	0.063
SS51210	50	78	22	1	78	52	0.29	0.16
SS51111	55	78	16	0.6	78	57	0.17	0.093
SS51211	55	90	25	1	90	57	0.46	0.25
SS51112	60	85	17	1	85	62	0.22	0.12
SS51212	60	95	26	1	95	62	0.52	0.28
SS51113	65	90	18	1	90	67	0.25	0.13
SS51213	65	100	27	1	100	67	0.58	0.31
SS51114	70	95	18	1	95	72	0.27	0.14
SS51214	70	105	27	1	105	72	0.61	0.33
SS51115	75	100	19	1	100	77	0.3	0.16
SS51215	75	110	27	1	110	77	0.65	0.35
SS51116	80	105	19	1	105	82	0.32	0.17
SS51216	80	115	28	1	115	82	0.72	0.38
SS51117	85	110	19	1	110	87	0.34	0.18
SS51217	85	125	31	1	125	88	0.94	0.5
SS51118	90	120	22	1	120	92	0.5	0.27
SS51218	90	135	35	1.1	135	93	1.3	0.69
SS51120	100	135	25	1	135	102	0.74	0.39
SS51220	100	150	38	1.1	150	103	1.73	0.92
SS51122	110	145	25	1	145	112	0.8	0.43
SS51124	120	155	25	1	155	122	0.86	0.46