

Bearing Designation	Dimensions									Ball Diameter	Load Rating		Weight
轴承型号	尺寸(mm)									钢球直径	载荷(KN)		重量
	d	B	C1	d1	d2	d3-6g	h	L1	L2		Dynamic	Static load	≈Kg
	H7										动载	静载	
COS3	3	6	4.5	5.1	14	M3	26	15	33	7.93	1.5	1.8	0.006
COS4	4	7	5.25	6.5	16	M4	30	19	38	9.52	2	2.9	0.011
COS5	5	8	6	7.7	18	M5	33	19	42	11.11	3.25	4.3	0.013
COS6	6	9	6.75	8.9	20	M6	36	21	46	12.7	4.25	6	0.02
COS8	8	12	9	10.3	24	M8	42	25	54	15.87	7.1	11	0.038
COS10	10	14	10.5	12.9	28	M10	48	28	63	19.05	9.8	17.4	0.055
COS12	12	16	12	15.4	32	M12	54	32	71	22.22	13.2	23.5	0.085
COS14	14	19	13.5	16.8	36	M14	60	36	79	25.4	17	28	0.14
COS16	16	21	15	19.3	42	M16	66	37	87	28.58	21.4	32	0.21
COS18	18	23	16.5	21.8	46	M18x1.5	72	41	95	31.75	26	42.5	0.28
COS20	20	25	18	24.3	50	M20x1.5	78	45	103	34.92	31	47.5	0.38
COS22	22	28	20	25.8	54	M22X1.5	84	48	112	38.1	42.2	57	0.48
COS25	25	31	22	29.5	60	M24x2	94	55	124	42.86	52.7	68	0.64
COS28	28	35	24	32.29	66	M27x2	103	62	136	47.63	58.8	79	0.949
COS30	30	37	25	34.8	70	M30x2	110	66	145	50.8	70.7	88	1.1