

Bearing Designation	Dimensions													Ball Diameter	Load Rating		Weight
轴承型号	尺寸(mm)													钢球直径	载荷(KN)		重量
	d	B	C1	d1	d2	d3-6H	h1	L3	(L4)	L5	d4	d5	sw		Dynamic	Static load	≈Kg
	H7														动载	静载	
PHS3	3	6	4.5	5.1	12	M3	21	10	27	3	9	7	7.93	14	1.8	4.5	0.006
PHS4	4	7	5.25	6.5	14	M4	24	12	31	4	9.5	8	9.52	13	2.2	5.6	0.013
PHS5	5	8	6	7.7	16	M5	27	11	35	4	11	9	11.11	13	2.5	6.6	0.016
PHS6	6	9	6.75	8.9	18	M6	30	13	39	5	13	11	12.7	13	3.2	8.1	0.025
PHS8	8	12	9	10.3	22	M8	36	16	47	5	16	14	15.87	14	5.4	12.6	0.043
PHS10	10	14	10.5	12.9	26	M10	43	20	56	6.5	19	17	19.05	13	7.5	16.6	0.072
PHS10F1	10	14	10.5	12.9	26	M10x1.25	43	20	56	6.5	19	17	19.05	13	7.5	16.6	0.072
PHS12	12	16	12	15.4	30	M12	50	23	65	6.5	22	19	22.22	13	10	22	0.107
PHS12/F2	12	16	12	15.4	30	M12X1.25	50	23	65	6.5	22	19	22.22	13	10	22	0.107
PHS14	14	19	13.5	16.8	34	M14	57	27	74	8	25	22	25.4	16	13	27.8	0.16
PHS14F1	14	19	13.5	16.8	34	M14x1.5	57	27	74	8	25	22	25.4	16	13	27.8	0.16
PHS15	15	20	14	18.1	36	M14	61	30	79	8	26	22	26.98	16	14.5	29	0.186
PHS16	16	21	15	19.3	38	M16	64	32	83	8	27	22	28.58	15	16	34.5	0.21
PHS16F1	16	21	15	19.3	38	M16X1.5	64	32	83	8	27	22	28.58	15	16	34.5	0.21
PHS17	17	22	16	20.6	40	M16x1.5	67	34	87	10	31	27	30.16	14	18	36	0.259
PHS18	18	23	16.5	21.8	42	M18X1.5	71	35	92	10	31	27	31.75	15	19.5	40.8	0.295
PHS20	20	25	18	24.3	46	M20x1.5	77	39	100	10	34	30	34.92	14	23	46.5	0.38
PHS22	22	28	20	25.8	50	M22X1.5	84	42	109	12	37	32	38.1	15	29	52.6	0.49
PHS25	25	31	22	29.5	60	M24x2	94	48	124	12	42	36	42.86	15	40.5	74.1	0.75
PHS28	28	35	24	32.29	66	M27x2	103	53	136	12	46	41	47.63	15	46.1	88.7	0.95
PHS30	30	37	25	34.8	70	M30x2	110	56	145	15	50	41	50.8	17	54.3	94	1.13