

Bearing Designation	Dimensions													Ball Diameter	Load Rating		Weight
轴承型号	尺寸(mm)													钢球直径	载荷(KN)		重量
	d	B	C1	d1	d2	d3-6H	h1	L3	(L4)	L5	d4	d5	sw		Dynamic Load	Static load	≈Kg
	H7		max												动载	静载	
PHS5EC	5	8	6	7.7	16	M5	27	11	35	4	11	9	11.11	13	3.3	6.2	0.016
PHS6EC	6	9	6.75	8.9	18	M6	30	13	39	5	13	11	12.7	13	4.7	7.8	0.025
PHS8EC	8	12	9	10.3	22	M8	36	16	47	5	16	14	15.87	14	7.7	13.2	0.043
PHS10EC	10	14	10.5	12.9	26	M10	43	20	56	6.5	19	17	19.05	13	10.4	17.3	0.072
PHS12EC	12	16	12	15.4	30	M12	50	23	65	6.5	22	19	22.22	13	13.5	22.7	0.107
PHS14EC	14	19	13.5	16.8	34	M14	57	27	74	8	25	22	25.4	16	17.2	28.2	0.16
PHS16EC	16	21	15	19.3	38	M16	64	32	83	8	27	22	28.58	15	21	35.1	0.21
PHS18EC	18	23	16.5	21.8	42	M18X1.5	71	35	92	10	31	27	31.75	15	25	43.2	0.295
PHS20EC	20	25	18	24.3	46	M20X1.5	77	39	100	10	34	30	34.92	14	29.8	50.3	0.38
PHS22EC	22	28	20	25.8	50	M22X1.5	84	42	109	12	37	32	38.1	15	36.2	63.9	0.49