

Bearing Designation	Dimensions									Ball Diameter	Load Rating		Weight
轴承型号	尺寸(mm)									钢球直径	载荷(KN)		重量
	d	B	C1	d1	d2	d3-6g	h	L1	L2		Dynamic Load	Static load	≈Kg
	H7										动载	静载	
POS3	3	6	4.5	5.1	12	M3	26	15	32	7.93	1.5	1.8	0.006
POS4	4	7	5.25	6.5	14	M4	30	19	37	9.52	2	2.9	0.011
POS5	5	8	6	7.7	16	M5	33	20	41	11.11	2.5	3.5	0.012
POS6	6	9	6.75	8.9	18	M6	36	22	45	12.7	3.2	4.8	0.019
POS8	8	12	9	10.3	22	M8	42	25	53	15.87	5.4	8.9	0.032
POS10	10	14	10.5	12.9	26	M10	48	29	61	19.05	7.5	12.5	0.054
POS10FI	10	14	10.5	12.9	26	M10x1.25	48	29	61	19.05	7.5	12.5	0.054
POS12	12	16	12	15.4	30	M12	54	33	69	22.22	10	15.8	0.085
POS12/F2	12	16	12	15.4	30	M12x1.25	54	33	69	22.22	10	15.8	0.085
POS14	14	19	13.5	16.8	34	M14	60	36	77	25.4	13	22.1	0.126
POS14F1	14	19	13.5	16.8	34	M14X1.5	60	36	77	25.4	13	22.1	0.126
POS15	15	20	14	18.1	36	M14	63	38	81	26.98	14.5	23.6	0.186
POS16	16	21	15	19.3	38	M16	66	40	85	28.58	16	25.9	0.185
POS16F1	16	21	15	19.3	38	M16X1.5	66	40	85	28.58	16	25.9	0.185
POS17	17	22	16	20.6	40	M16X1.5	69	42	89	30.16	18	28.4	0.259
POS18	18	23	16.5	21.8	42	M18x1.5	72	44	93	31.75	19.5	30.8	0.26
POS20	20	25	18	24.3	46	M20X1.5	78	47	101	34.92	23	36.2	0.34
POS22	22	28	20	25.8	50	M22x1.5	84	51	109	38.1	29	42.6	0.435
POS25	25	31	22	29.5	60	M24x2	94	57	124	42.86	40.5	74.1	0.65
POS28	28	35	24	32.29	66	M27x2	103	62	136	47.63	46.1	88.7	0.875
POS30	30	37	25	34.8	70	M30x2	110	66	145	50.8	54.3	94	1.07