

Bearing Designation	Dimensions(mm/in)						
轴承	尺寸(mm/英寸)						
	d+0.03	B	C1	d2	d3	h	L1
	-0.01				UNF-2A		
PMX5T	7.938	11.11	8.31	22.86	5/16-24	47.63	30.15
PMX5T	0.3125	0.437	0.327	0.9	5/16-24	1.875	1.187
PMX6T	9.525	12.7	10.57	26.03	2003/8/24	49.22	30.15
PMX6T	0.375	0.5	0.416	1.025	2003/8/24	1.938	1.187
PMX7T	11.112	14.27	11.48	29.21	7/16-20	53.98	32.54
PMX7T	0.4375	0.562	0.452	1.15	7/16-20	2.125	1.281
PMX8T	12.7	15.88	13.8	33.96	2001/2/20	61.92	37.29
PMX8T	0.5	0.625	0.515	1.337	2001/2/20	2.438	1.468
PMX10T	15.875	19.05	14.66	38.74	2005/8/18	66.68	39.67
PMX10T	0.625	0.75	0.577	1.525	2005/8/18	2.625	1.562
PMX12T	19.05	22.23	16.27	45.09	2003/4/16	73.03	42.85
PMX12T	0.75	0.875	0.64	1.775	2003/4/16	2.875	1.687

	Ball Diameter	Load Rating	Weight
	钢球直径	载荷(KN)	重量
(L2)			≈ kg
59.06	15.06	14	0.039
2.325	0.593	14	0.039
62.23	17.45	12	0.061
2.45	0.687	12	0.061
68.58	19.83	14	0.083
2.7	0.781	14	0.083
78.9	22.22	12	0.126
3.106	0.875	12	0.126
86.05	26.97	16	0.192
3.387	1.062	16	0.192
95.57	31.75	14	0.289
3.762	1.25	14	0.289