

Principal dimensions (mm)			Basic load ratings (kN)		Pu	Speed ratings (rpm)		Bearing+ Withdrawal	Designation		Dimensions (mm)												Abutment and fillet dimensions (mm)				Value			
基本尺寸			基本额定负荷		疲劳负荷 极限	额定转速		轴承+ 退卸套	型号		尺寸												安装尺寸				计算系数			
d ₁	D	B	d _{yc}	stc		Speed Ratings	Limiting Speed		Bearing	Withdrawal sleeves	d ₁	d ₂	D1	B ₁	B ₂ ¹⁾	G	G ₁	b	k	r _{1,2}	d _a	Da	r _a	e	Y1	Y2	Y ₀			
			Cr	Cor								~	~							Min	Max	Max	Max							
320	620	224	5100	7800	550	560	800	315	*23268CAK/W33	AOH3268G	320	426	528	264	273	Tr360×5	38	22.3	12	6	366	594	5	0.35	1.9	2.9	1.8			
320	620	224	5100	7800	550	560	800	315	*23268CAK/W33	AOH3268G	320	426	528	264	273	Tr360×5	38	22.3	12	6	366	594	5	0.35	1.9	2.9	1.8			
340	650	232	5400	8300	570	530	750	345	*23272CAK/W33	AOH3272G	340	447	552	274	283	Tr380×5	40	22.3	12	6	386	624	5	0.35	1.9	2.9	1.8			
360	680	240	5850	9150	620	500	750	390	*23276CAK/W33	AOH3276G	360	471	581	284	294	Tr400×5	42	22.3	12	6	406	654	5	0.35	1.9	2.9	1.8			
380	720	256	6550	10400	680	480	670	470	*23280CAK/W33	AOH3280G	380	499	615	302	312	Tr420×5	44	22.3	12	6	426	694	5	0.35	1.9	2.9	1.8			
400	760	272	7350	11600	765	450	630	550	*23284CAK/W33	AOH3284G	400	525	649	321	331	Tr440×5	46	22.3	12	7.5	452	728	6	0.35	1.9	2.9	1.8			
420	790	280	7800	12500	800	430	600	620	*23288CAK/W33	AOHX3288G	420	547	676	330	341	Tr460×5	48	22.3	12	7.5	472	758	6	0.35	1.9	2.9	1.8			
440	830	296	8500	13700	880	400	560	725	*23292CAK/W33	AOHX3292G	440	572	706	349	360	Tr480×5	50	22.3	12	7.5	492	798	6	0.35	1.9	2.9	1.8			
440	830	296	8500	13700	880	400	560	725	*23292CAK/W33	AOHX3292G	440	572	706	349	360	Tr480×5	50	22.3	12	7.5	492	798	6	0.35	1.9	2.9	1.8			
460	870	310	9300	15000	950	380	530	860	*23296CAK/W33	AOHX3296G	460	600	741	364	376	Tr500×5	52	22.3	12	7.5	512	838	6	0.35	1.9	2.9	1.8			
480	920	336	10600	17300	1060	360	500	1020	*232/500CAK/W33	AOHX32/500G	480	631	779	393	405	Tr530×6	54	22.3	12	7.5	532	888	6	0.35	1.9	2.9	1.8			
500	980	355	11100	20400	1220	300	480	1285	232/530CAK/W33	AOH32/530G	500	668	836	412	424	Tr560×6	57	22.3	12	9.5	570	940	8	0.35	1.9	2.9	1.8			
530	1030	365	11500	22000	1400	280	430	1500	232/560CAK/W33	AOHX32/560G	530	704	878	422	434	Tr600×6	57	22.3	12	9.5	600	990	8	0.35	1.9	2.9	1.8			
570	1090	388	13100	25500	1560	260	400	1760	232/600CAK/W33	AOHX32/600G	570	752	929	445	459	Tr630×6	57	22.3	12	9.5	640	1050	8	0.35	1.9	2.9	1.8			
630	1220	438	15400	30500	1700	220	360	2500	232/670CAK/W33	AOH32/670G	630	830	1028	500	514	Tr710×7	62	22.3	12	12	718	1172	10	0.35	1.9	2.9	1.8			
630	1220	438	15400	30500	1700	220	360	2500	232/670CAK/W33	AOH32/670G	630	830	1028	500	514	Tr710×7	62	22.3	12	12	718	1172	10	0.35	1.9	2.9	1.8			
670	1280	450	17600	34500	2000	200	320	2880	232/710CAK/W33	AOH32/710G	670	875	1017	515	531	Tr750×7	65	22.3	12	12	758	1232	10	0.35	1.9	2.9	1.8			
710	1360	475	18700	36500	2120	190	300	3255	232/750CAKF/W33	AOH32/750	710	938	1163	540	556	Tr800×7	65	22.3	12	15	808	1302	12	0.35	1.9	2.9	1.8			