

Bearing Designation	Dimensions(mm/in)								Ball Diameter	Load Rating	Weight
轴承	尺寸(mm/英寸)								钢球直径	载荷(KN)	重量
	d+0.03	B	C1	d2	d3	h	L1	(L2)			≈ kg
	-0.01				UNF-2A						
RJMX6T	9.525	12.7	10.31	25.4	4/28	49.22	31.75	61.92	18.26	12	0.035
RJMX6T	0.375	0.5	0.406	1	4/28	1.938	1.25	2.437	0.719	12	0.035
RJMX7T	11.112	14.27	11.1	28.58	5/16	53.98	34.93	68.27	20.62	14	0.041
RJMX7T	0.4375	0.562	0.437	1.125	5/16	2.125	1.375	2.678	0.812	14	0.041
RJMX8T	12.7	15.88	12.7	33.32	8/24	61.92	38.1	78.58	23.8	12	0.063
RJMX8T	0.5	0.625	0.5	1.312	8/24	2.438	1.5	3.093	0.937	12	0.063
RJMX10T	15.875	19.05	14.27	38.1	7/16	66.68	41.28	85.73	28.58	16	0.108
RJMX10T	0.625	0.75	0.562	1.5	7/16	2.625	1.625	3.375	1.125	16	0.108
RJMX12T	19.05	22.23	17.45	44.45	4/16	73.02	44.45	95.25	33.33	14	0.136
RJMX12T	0.75	0.875	0.687	1.75	4/16	2.875	1.75	3.75	1.312	14	0.136