

Bearing Designation	Dimensions(mm/in)										Ball Diameter	Load Rating	Weight
轴承	尺寸(mm/英寸)										钢球直径	载荷(KN)	重量
	d2	C1	d3	h	L1	(L4)	N	S	P	L			≈ kg
			UNF-2A				UNF-2A						
CM3TY	15.88	5.94	10-32	31.75	19.05	39.69	10-32	11.1	12.7	25.8	22	4.4	0.018
CM3TY	0.625	0.234	10-32	1.25	0.75	1.562	10-32	0.437	0.5	1.016	22	4.4	0.018
CM4TY	19.05	6.35	4/28	39.67	25.4	49.2	4/28	12.7	14.27	26.18	20	8.2	0.022
CM4TY	0.75	0.25	4/28	1.562	1	1.937	4/28	0.5	0.562	1.031	20	8.2	0.022
CM5TY	22.23	7.92	5/16	47.63	31.75	58.75	5/16	15.06	17.45	30.96	21	10.2	0.045
CM5TY	0.875	0.312	5/16	1.875	1.25	2.312	5/16	0.593	0.687	1.219	21	10.2	0.045
CM6TY	25.4	9.11	8/24	49.23	31.75	61.92	8/24	20.62	23	39.67	23	14	0.068
CM6TY	1	0.359	8/24	1.938	1.25	2.437	8/24	0.812	0.906	1.562	23	14	0.068
CM7TY	28.58	10.31	7/16	53.98	34.93	68.27	7/16	23.8	26.97	44.45	22	17.6	0.108
CM7TY	1.125	0.406	7/16	2.125	1.375	2.678	7/16	0.937	1.062	1.75	22	17.6	0.108
CM8TY	33.33	11.5	2/20	61.93	38.1	78.58	2/20	25.4	28.58	50.8	24	23.7	0.158
CM8TY	1.312	0.453	2/20	2.438	1.5	3.093	2/20	1	1.125	2	24	23.7	0.158
CM10TY	38.1	12.3	8/18	66.68	41.28	85.73	8/18	34.93	38.1	63.5	26	25.7	0.276
CM10TY	1.5	0.484	8/18	2.625	1.625	3.375	8/18	1.375	1.5	2.5	26	25.7	0.276
CM12TY	44.45	15.06	4/16	73.03	44.45	95.25	4/16	41.28	46.02	76.2	23	42.4	0.467
CM12TY	1.75	0.593	4/16	2.875	1.75	3.75	4/16	1.625	1.812	3	23	42.4	0.467