

Designation (Without inner ring)	Mass ≈g	With binner ring Designation	Mass ≈g	Dimensions(mm) 尺寸(毫米)						Basic load ratings 基本额定负荷					Limit speed n _{1grease} (min-1)
型号(无内圈)	质量(克)	型号(有内圈)	质量(克)	D	d	C	B	d _a	r min.	动态 dyc Cr	静态C ₀	动态 dyc C _w	动态 dyc F _{rperm}	静态 stc F _{orperm}	极限转速
STO6ZZ	8.5	STO6ZZX	-	19	6	13.8	14	15	0.3	1210	1450	969	1180	1390	12000
STO8ZZ	12.5	STO8ZZX	17	24	8	13.8	14	18	0.3	1310	1700	1120	1700	1830	9900
STO10ZZ	21	STO10ZZX	26	30	10	15.8	16	23	0.3	2340	2380	2010	2170	2560	9400
STO12ZZ	42	STO12ZZX	49	32	12	15.8	16	25	0.3	2520	2680	2050	2140	2630	8100
STO15ZZ	49	STO15ZZX	57	35	15	15.8	16	30	0.3	2900	3440	2130	1920	2720	6300
STO17ZZ	50	STO17ZZX	63	40	17	19.8	20	33	0.3	4270	5240	3190	3010	4340	5600
STO20ZZ	88	STO20ZZX	107	47	20	19.8	20	37	0.3	4500	5710	3530	4380	5280	4900
STO25ZZ	130	STO25ZZX	152	52	25	19.8	20	42	0.3	5040	6990	3690	4450	5640	4100
STO30ZZ	150	STO30ZZX	177	62	30	24.8	25	52	0.6	7490	11500	5170	6050	8140	3200
STO35ZZ	255	STO35ZZX	308	72	35	24.8	25	56	0.6	7910	12700	5820	8810	10200	2900
STO40ZZ	375	STO40ZZX	441	80	40	25.8	26	64	0.6	8720	15200	6020	9330	10800	2400
STO45ZZ	420	STO45ZZX	530	85	45	25.8	26	69	0.6	9060	16500	6050	9530	10900	2200
STO50ZZ	453	STO50ZZX	576	90	50	25.8	26		0.6						