

Bearing Designation	Mass ≈g	With eccentric collar Designation	Mass ≈g	尺寸(毫米) Dimensions														Eccentric collar			Drive fit lubrication nipple	Nut tightening torque	Basic load ratings (KN)		Fatigue limit load C _{10LW} N	Speed n ₀₀ min ⁻¹		
				D	d ₁ h ₇	B	B ₁ max.	B ₂	B ₃	C	C ₁	r min.	d ₂	d ₃	G	l ₀	W	偏心套					油嘴	螺母拧紧扭矩			基本额定负荷	
																		d ₄ h ₉	B ₄	e							dyc	stc
轴承型号	质量	带偏心套型号	质量	(mm)																			极限疲劳 载荷		极限转速			
(克)	(克)		(克)																									
KR16 ⁽¹⁾	19	-	-	16	6	28	12.2	16	-	11	0.6	0.15	12.5	-	M6(×1)	8	-	-	-	-	NIPA1	3	3150	3300	415	14000		
KR16-PP ⁽¹⁾	18	KRE16-PP ⁽¹⁾	20	16	6	28	12.2	16	-	11	0.6	0.15	12.5	-	M6(×1)	8	-	9	7	0.5	NIPA1	3	3150	3300	415	14000		
KR16-SK-PP ⁽²⁾	19	-	-	16	6	28	12.2	16	-	11	0.6	0.15	12.5	-	M6(×1)	8	4	-	-	-	-	3	3150	3300	415	14000		
KRV16-PP ⁽¹⁾	19	-	-	16	6	28	12.2	16	-	11	0.6	0.15	12.5	-	M6(×1)	8	-	-	-	-	NIPA1	3	4900	6500	860	3800		
KR19 ⁽¹⁾	29	-	-	19	8	32	12.2	20	-	11	0.6	0.15	15	-	M8(×1.25)	10	-	-	-	-	NIPA1	8	3500	3900	485	11000		
KR19-PP ⁽¹⁾	29	KRE19-PP ⁽¹⁾	32	19	8	32	12.2	20	-	11	0.6	0.15	15	-	M8(×1.25)	10	-	11	9	0.5	NIPA1	8	3500	3900	485	11000		
KR19-SK-PP ⁽²⁾	29	-	-	19	8	32	12.2	20	-	11	0.6	0.15	15	-	M8(×1.25)	10	4	-	-	-	-	8	3500	3900	485	11000		
KRV19-PP ⁽¹⁾	31	-	-	19	8	32	12.2	20	-	11	0.6	0.15	15	-	M8(×1.25)	10	-	-	-	-	NIPA1	8	5400	7900	1040	3100		
KR22	45	-	-	22	10	36	13.2	23	-	12	0.6	0.3	17.5	-	M10×1	12	5	-	-	-	NIPA1×4.5	15	4500	5200	650	8000		
KR22-PP	43	KRE22-PP	47	22	10	36	13.2	23	-	12	0.6	0.3	17.5	-	M10×1	12	5	13	10	0.5	-	15	4500	5200	650	8000		
KRV22-PP	45	-	-	22	10	36	13.2	23	-	12	0.6	0.3	17.5	-	M10×1	12	5	-	-	-	NIPA1×4.5	15	6200	9100	1110	2600		
KR26	59	-	-	26	10	36	13.2	23	-	12	0.6	0.3	17.5	-	M10×1	12	5	-	-	-	NIPA1×4.5	15	5100	6200	770	8000		
KR26-PP	57	KRE26-PP	62	26	10	36	13.2	23	-	12	0.6	0.3	17.5	-	M10×1	12	5	13	10	0.5	NIPA1×4.5	15	5100	6200	770	8000		
KRV26-PP	59	-	-	26	10	36	13.2	23	-	12	0.6	0.3	17.5	-	M10×1	12	5	-	-	-	NIPA1×4.5	15	7300	11300	1380	2600		
KR30	92	-	-	30	12	40	15.2	25	6	14	0.6	0.6	23	3	M12×1.5	13	6	-	-	-	NIPA1×4.5	22	6800	8400	1070	5500		
KR30-PP	88	KRE30-PP	93	30	12	40	15.2	25	6	14	0.6	0.6	23	3	M12×1.5	13	6	15	11	0.5	NIPA1×4.5	22	6800	8400	1070	5500		
KRV30-PP	91	-	-	30	12	40	15.2	25	6	14	0.6	0.6	23	3	M12×1.5	13	6	-	-	-	NIPA1×4.5	22	9500	14600	1840	2100		
KR32	103	-	-	32	12	40	15.2	25	6	14	0.6	0.6	23	3	M12×1.5	13	6	-	-	-	NIPA1×4.5	22	7100	8900	1140	5500		
KR32-PP	98	KRE32-PP	104	32	12	40	15.2	25	6	14	0.6	0.6	23	3	M12×1.5	13	6	15	11	0.5	NIPA1×4.5	22	7100	8900	1140	5500		
KRV32-PP	101	-	-	32	12	40	15.2	25	6	14	0.6	0.6	23	3	M12×1.5	13	6	-	-	-	NIPA1×4.5	22	10000	15800	1990	2100		
KR35	173	-	-	35	16	52	19.6	32.5	8	18	0.8	0.6	27.6	3	M16×1.5	17	8	-	-	-	NIPA2×7.5	58	9800	14100	1700	3600		
KR35-PP	164	KRE35-PP	177	35	16	52	19.6	32.5	8	18	0.8	0.6	27.6	3	M16×1.5	17	8	20	14	1	NIPA2×7.5	58	9800	14100	1700	3600		
KRV35-PP	166	-	-	35	16	52	19.6	32.5	8	18	0.8	0.6	27.6	3	M16×1.5	17	8	-	-	-	NIPA2×7.5	58	12800	23000	2900	1600		
KR40	247	-	-	40	18	58	21.6	36.5	8	20	0.8	1	31.5	3	M18×1.5	19	8	-	-	-	NIPA2×7.5	87	10900	15500	1850	2900		
KR40-PP	239	KRE40-PP	255	40	18	58	21.6	36.5	8	20	0.8	1	31.5	3	M18×1.5	19	8	22	15	1	NIPA2×7.5	87	10900	15500	1850	2900		
KRV40-PP	247	-	-	40	18	58	21.6	36.5	8	20	0.8	1	31.5	3	M18×1.5	19	8	-	-	-	NIPA2×7.5	87	14800	26500	3050	1400		
KR47-PP	381	KRE47-PP	400	47	20	66	25.6	40.5	9	24	0.8	1	36.5	4	M20×1.5	21	10	24	18	1	NIPA2×7.5	120	15500	25500	3000	2400		
KRV47-PP	390	-	-	47	20	66	25.6	40.5	9	24	0.8	1	36.5	4	M20×1.5	21	10	-	-	-	NIPA2×7.5	120	20600	42000	5200	1300		
KR52-PP	454	KRE52-PP	473	52	20	66	25.6	40.5	9	24	0.8	1	36.5	4	M20×1.5	21	10	24	18	1	NIPA2×7.5	120	16700	29000	3400	2400		
KRV52-PP	463	-	-	52	20	66	25.6	40.5	9	24	0.8	1	36.5	4	M20×1.5	21	10	-	-	-	NIPA2×7.5	120	22600	48000	5900	2300		
KR62-PP	770	KRE62-PP	798	62	24	80	30.6	49.5	11	29	0.8	1	44	4	M24×1.5	25	14	28	22	1	NIPA3×9.5	220	26500	48000	6100	1900		
KRV62-PP	787	-	-	62	24	80	30.6	49.5	11	29	0.8	1.1	44	4	M24×1.5	25	14	-	-	-	NIPA3×9.5	220	34000	75000	9800	1100		
KR72-PP	1010	KRE72-PP	1038	72	24	80	30.6	49.5	11	29	0.8	1.1	44	4	M24×1.5	25	14	28	22	1	NIPA3×9.5	220	28000	53000	6700	1900		
KRV72-PP	1027	-	-	72	24	80	30.6	49.5	11	29	0.8	1.1	44	4	M24×1.5	25	14	-	-	-	NIPA3×9.5	220	36500	85000	11100	1100		
KR80-PP	1608	KRE80-PP	1665	80	30	100	37	63	15	35	1	1.1	53	4	M30×1.5	32	14	35	29	1.5	NIPA3×9.5	450	39000	77000	9900	1300		
KRV80-PP	1636	-	-	80	30	100	37	63	15	35	1	1.1	53	4	M30×1.5	32	14	-	-	-	NIPA3×9.5	450	49500	117000	15300	850		
KR90-PP	1975	KRE90-PP	2032	90	30	100	37	63	15	35	1	1.1	53	4	M30×1.5	32	14	35	29	1.5	NIPA3×9.5	450	41000	83000	10600	1300		
KRV90-PP	2003	-	-	90	30	100	37	63	15	35	1	1.1	53	4	M30×1.5	32	14	-	-	-	NIPA3×9.5	450	52000	129000	16900	850		