

Bearing Designation	Dimensions(mm/in)								Ball Diameter	Load Rating	Weight
轴承	尺寸(mm/英寸)								钢球直径	载荷(KN)	重量
	d	B	C1	d2	d3	h	l1	(l2)			≈ kg
					UNF-2A						
CMX8T	12.7	15.88	11.5	33.32	2/20	61.92	38.1	78.58	23.8	12	0.108
CMX8T	0.5	0.625	0.453	1.312	2/20	2.438	1.5	3.093	0.937	12	0.108
CMX10-8T	12.7	19.05	12.29	38.1	8/18	66.68	41.28	85.73	28.57	16	0.136
CMX10-8T	0.5	0.75	0.484	1.5	8/18	2.625	1.625	3.375	1.125	16	0.136
CMX10T	15.88	19.05	12.29	38.1	8/18	66.68	41.28	85.73	28.57	16	0.163
CMX10T	0.625	0.75	0.484	1.5	8/18	2.625	1.625	3.375	1.125	16	0.136
CMX12-8T	12.7	22.23	15.06	44.45	4/16	73.02	44.45	95.25	33.33	14	0.258
CMX12-8T	0.5	0.875	0.593	1.75	4/16	2.875	1.75	3.75	1.312	14	0.258
CMX12-10T	15.875	22.23	15.06	44.45	4/16	73.02	44.45	95.25	33.33	14	0.258
CMX12-10T	0.625	0.875	0.593	1.75	4/16	2.875	1.75	3.75	1.312	14	0.258
CMX12T	19.05	22.23	15.06	44.45	4/16	73.02	44.45	95.25	33.33	14	0.258
CMX12T	0.75	0.875	0.593	1.75	4/16	2.875	1.75	3.75	1.312	14	0.258