

Bearing Designation	Dimensions													Ball Diameter	Load Rating		Weight
轴承型号	尺寸(mm)													钢球直径	载荷(KN)		重量
	d +0.038	B	C1	d1	d2	d3	h1	L3	(L4)	L5	d4	d5	sw		Dynamic	Static load	≈Kg
	-0.012					UNF-2B									动载	静载	
PHSB3	4.826	7.92	6.35	7.77	15.88	10-32	26.97	12.7	34.91	4.75	10.31	7.92	11.11	10	2.8	7.4	0.015
PHSB4	6.35	9.53	7.14	9.02	19.05	4/28	33.32	17.45	42.85	4.75	11.89	9.53	12.7	13	4.8	11.2	0.025
PHSB5	7.938	11.1	8.74	11.35	22.23	5/16	34.93	17.45	46.03	4.75	12.7	11.1	15.87	10	5.9	13.8	0.036
PHSB6	9.525	12.7	10.31	13.13	25.4	8/24	41.28	20.62	53.98	6.35	17.45	14.27	18.26	9	8.2	18.2	0.061
PHSB7	11.112	14.27	11.1	14.88	28.58	7/16	46.02	23.8	60.3	6.35	19.05	15.88	20.62	11	10	22	0.081
PHSB8	12.7	15.88	12.7	17.73	33.32	2/20	53.98	26.97	70.64	6.35	22.22	19.05	23.8	9	15	31.7	0.133
PHSB10	15.875	19.05	14.27	21.31	38.1	8/18	63.5	34.92	82.55	7.92	25.4	22.22	28.57	11	18	35.1	0.19
PHSB12	19.05	22.23	17.45	24.84	44.45	4/16	73.03	39.67	95.25	7.92	28.58	25.4	33.33	10	27	49.6	0.285
PHSB16	25.4	34.93	25.4	32.23	69.85	4/12	104.78	53.98	139.7	11.1	44.45	38.1	47.62	14	60	101	1