

Bearing Designation	Dimensions(mm/in)								Ball Diameter	Load Rating	Weight
轴承	尺寸(mm/英寸)								钢球直径	载荷(KN)	重量
	d+0.03	B	C1	d2	d3	h	L1	(L2)			≈ kg
	-0.01				UNF-2A						
RRSMX6T	9.525	12.7	10.31	28.58	7/16-20	53.98	34.93	68.27	18.26	12	0.072
RRSMX6T	0.375	0.5	0.406	1.125	7/16-20	2.125	1.375	2.687	0.719	12	0.072
RRSMX7T	11.112	14.27	11.1	33.32	1/2-20	61.92	38.1	78.58	20.62	14	0.112
RRSMX7T	0.4375	0.562	0.437	1.312	1/2-20	2.438	1.5	3.093	0.812	14	0.112
RRSMX8T	12.7	15.88	12.7	38.1	5/8-18	66.68	41.28	85.73	23.8	12	0.173
RRSMX8T	0.5	0.625	0.5	1.5	5/8-18	2.625	1.625	3.375	0.937	12	0.173
RRSMX10T	15.875	19.05	14.27	44.45	3/4-16	73.03	44.45	95.25	28.58	16	0.273
RRSMX10T	0.625	0.75	0.562	1.75	3/4-16	2.875	1.75	3.75	1.125	16	0.273