

Bearing Designation	Dimensions(mm/in)								Ball Diameter	Load Rating	Weight
轴承	尺寸(mm/英寸)								钢球直径	载荷(KN)	重量
	d+0.03	B	C1	d2	d3	h	L1	(L2)			≈ kg
	-0.01				UNF-2A						
RSMX3T	0.19	0.312	0.25	0.75	1/4-28	1.562	1	1.937	0.437	10	0.019
RSMX4T	0.25	0.375	0.281	0.875	5/16-24	1.875	1.25	2.312	0.5	13	0.032
RSMX5T	0.3125	0.437	0.344	1	3/8-24	1.938	1.25	2.437	0.625	10	0.05
RSMX6T	0.375	0.5	0.406	1.125	7/16-20	2.125	1.375	2.687	0.719	9	0.072
RSMX7T	0.4375	0.562	0.437	1.312	1/2-20	2.438	1.5	3.093	0.812	11	0.112
RSMX8T	0.5	0.625	0.5	1.5	5/8-18	2.625	1.625	3.375	0.937	9	0.173
RSMX10T	0.625	0.75	0.562	1.75	3/4-16	2.875	1.75	3.75	1.125	11	0.273
RSMX12T	0.75	0.875	0.687	2	3/8-14	3.375	1.875	4.375	1.312	10	0.416