

Bearing Designation	Dimensions(mm)																Static Load ratings	Weight
轴承	尺寸(mm)																静载荷	重量
																	KN	≈ kg
	d	d3-6g	d2	d3	I1	I2	S1	L	L1	L2	L3	D1	D2	D3	S2			
SQZ5-RS	5	M5	9	19	8	11	7	46	24	4	9	11	17	9	2.8		15	0.025
SQZ6-RS	6	M6	10	20	11	12.2	8	55.2	28	5	10	13	20	11	3.7		15	0.041
SQZ8-RS	8	M8	12	24	12	16	10	65	32	5	12.5	16	24	14	5.8		15	0.075
SQZ10-RS	10	M10X1.25	14	30	15	19.5	11	74.5	35	6.5	15	19	28	17	8.4		15	0.12
SQZ12-RS	12	M12X1.25	17	32	17	21	15	84	40	6.5	17.5	22	32	19	11		15	0.18
SQZ14-RS	14	M14X1.5	19	38	22	23.5	17	103	45	8	20	25	36	22	15		11	0.27
SQZ16-RS	16	M16x1.5	22	44	23	25.5	19	112	50	8	22	27	40	22	15		11	0.36
SQZ18-RS	18	M18X1.5	23	45	25	31	20	130.5	58	10	25	31	45	27	19		11	0.54
SQZ20-RS	20	M20x1.5	27	50	25	29	24	133	63	10	27.5	34	45	30	19		7.5	0.57
SQZ22-RS	22	M22x1.5	27	52	26	33	24	145	70	12	30	37	50	32	23		7.5	0.76