

Type	Mounting Dimensions (mm)					Block Dimensions (mm)							Rail Size						Load capacity					Weight			
轴承型号	安装尺寸					分形维数						导轨尺寸						Dynamic	Sationary	Stationary moment(k gf.M)	Stationary moment(k gf.M)	Stationary moment(k gf.M),br>	重量				
						B×J	M×L	L1	J1	K	T	Nipple	Nipple	Nipple	Width	Height	Pitch						Bolt Hole	G	Max.lengt h	Blocks	Slide shaft
	短节	短节	短节	宽度	高度							节径	螺钉孔	最大长度	动态	静态	静						静		静	滑块	滑动轴
	H	E	W2	W	L							Mounting	T1	N	W1	H1	F						d×D×h		Of rail	C(kgff)	Co(kgff)
SBG20SLL	30	3.6	11.5	44	90	32*36	M5*6	66.8	8.4	26.5	8	M6*0.75	4.45	12	20	17.5	60	6*9.5*8.5	20	3040	2170	3240	31	35	35	0.4	2.16
SBG25SLL	40	5.2	12	48	102.5	35*50	M6*8	78.6	14.3	35.5	8	M6*0.75	9.95	12	23	21.8	60	7*11*9	20	4480	2770	4680	48	54	53	0.8	3.14
SBG30SLL	45	5.5	15.5	60	120.5	40*60	M8*10	93	16.5	39.5	8	M6*0.75	11.5	12	28	25	80	9*14*12	20	4440	3800	6375	80	86	85	1.2	4.5
SBG35SLL	55	7.5	17	70	135	50*72	M8*12	105.8	16.9	47.5	10	M6*0.75	16.5	12	34	29	80	9*14*12	20	4440	5120	8310	136	144	141	2	6.3
SBG45SLL	70	8	19.5	86	171	60*80	M10*17	129.8	24.5	62	15	PT1/8	20.3	16	45	38	105	14*20*17	225	4450	8200	12954	264	251	248	3.8	10.9
SBG55SLL	80	10.5	22.5	100	201	75*95	M12*18	156.1	30.55	69.5	18	PT1/8	22	16	53	45	120	16*23*20	30	4480	12130	18660	449	435	426	6	14.9
SBG65SLL	90	17.5	28.5	126	246	76*120	M16*20	206.5	43.25	72.5	23	PT1/8	15	16	63	58.5	150	18*26*22	35	4390	19580	29170	834	850	830	10.5	21.3