

型号	基本尺寸 Dimensions (mm)															单位/Unit:mm		基本额定重量	界限重量	预压重量	轴方向刚性	启动力矩	锁紧螺母 Lock nut			重量	轴端尺寸 Dimensions of shaft end		
Designation	d	D	D1	D2	L	L1	L2	A	W	X	Y	Z	d1	l	V	P	Q	The basic load rating	Permissible axial load (N)	Preload (N)	Axial rigidity (N/um)	Staring torque (N-cm)	M	D3	L3	Weight (Kg)	d	L4	L5
WBK 20DF	20	75	106	72	60	32	15	80	88	9	14	8.5	45	3	58	M5	10	21900	26600	2150	750	14.0	M20×1	40	18	1.9	20	81	23
WBK 25DF	25	85	130	90	66	33	18	100	110	11	17.5	11	57	4	70	M6	12	28500	40500	3150	1000	23.0	M25×1.5	45	20	3.1	25	89	26
WBK 25DFD	25	85	130	90	81	48	18	100	110	11	17.5	11	57	4	70	M6	12	46500	81500	4300	1470	31.0	M25×1.5	45	20	3.4	25	104	26
WBK 30DF	30	85	130	90	66	33	18	100	110	11	17.5	11	57	4	70	M6	12	29200	43000	3350	1030	24.0	M30×1.5	50	20	3.0	30	89	26
WBK 30DFD	30	85	130	90	81	48	18	100	110	11	17.5	11	57	4	70	M6	12	47500	86000	4500	1520	33.0	M30×1.5	50	20	3.3	30	104	26
WBK 35DF	35	95	142	102	66	33	18	106	121	11	17.5	11	69	4	80	M6	12	31000	50000	3800	1180	28.0	M35×1.5	55	22	3.4	35	92	30
WBK 35DFD	35	95	142	102	81	48	18	106	121	11	17.5	11	69	4	80	M6	12	50500	100000	5200	1710	37.0	M35×1.5	55	22	4.3	35	107	30
WBK 40DF	40	95	142	102	66	33	18	106	121	11	17.5	11	69	4	80	M6	12	31500	52000	3900	1230	28.0	M40×1.5	60	22	3.6	40	92	30
WBK 40DFD	40	95	142	102	81	48	18	106	121	11	17.5	11	69	4	80	M6	12	51500	104000	5300	1810	38.0	M40×1.5	60	22	4.2	40	107	30