

型号	额定扭矩 [N·m]	最大容许误差		最高转速 [min-1]	扭转弹性 常数	轴向弹性 常数	转动惯量	质量 [kg]	d1 . d2			D	N	L	LF	S	F	K	M
Designation	Rated torque	偏心 Eccentricity [mm]	轴向位移 Axial displacement [mm]	Max rotating speed	Torsional elasticity constant	Axial elastic constant	Rotational inertia	Weight	底孔 bottom hole	最小 min	最大 max								
LC-BS-05S	20	1	±0.6	25000	16000	43	0.11x10-3	0.3	7	8	20	56	32	45	20	5	11	24	4-M5x22
LC-BS-06S	40	1	±0.8	20000	29000	45	0.30x10-3	0.5	7	8	25	68	40	56	25	6	10	30	4-M6x25
LC-BS-08S	80	1	±1.0	17000	83000	60	0.87x10-3	1	10	11	35	82	54	66	30	6	11	38	4-M6x29
LC-BS-09S	180	1	±1.2	15000	170000	122	1.60x10-3	1.4	10	11	38	94	58	68	30	8	21	42	4-M8x36
LC-BS-10S	250	1	±1.4	13000	250000	160	2.60x10-3	2.1	15	16	42	104	68	80	35	10	16	48	4-M8x36
LC-BS-12S	450	1	±1.6	11000	430000	197	6.50x10-3	3.4	18	19	50	126	78	91	40	11	23	54	4-M10x45
LC-BS-14S	800	1	±1.8	9500	780000	313	9.90x10-3	4.9	20	22	60	144	88	102	45	12	31	61	4-M12x54