

Designation	d1·d2[mm]		d1·d2 standard aperture&corresponding transmission of torque									Cinch bolt			Rotational inertia
型号	d1·d2[mm]		d1·d2标准孔径[mm]和相应的可传递的扭矩 [N·m]									胀紧螺栓			转动惯量
	min	max	D	dH	L	L1,L2	L3	E	B	S	a	M	Locking torque	M1	
	最小	最大											锁紧扭矩 [N·m]		[kg·m2]
LC-EA-030A	6	14	30	10.5	50	18.5	13.5	13	10	1.5	2	M3	1.5	M3	0.04x10-4
LC-EA-040A	10	20	40	18	66	25	18	16	12	2	3	M4	3.4	M4	0.19x10-4
LC-EA-055A	14	28	55	27	78	30	22	18	14	2	3	M5	7	M5	0.78x10-4
LC-EA-065A	19	38	65	30	90	35	27	20	15	2.5	4	M5	7	M5	1.70x10-4
LC-EA-080A	20	48	80	38	114	45	35	24	18	3	4	M6	14	M6	5.17x10-4
LC-EA-095A	28	50	95	46	126	50	35	26	20	3	4	M8	30	M8	11.17x10-4
LC-EA-105A	30	55	105	51	140	56	41	28	21	3.5	4	M10	68	M10	18.81x10-4