

Designation	Rated torque [N·m]	最大容许误差 Margin of error			Moment of inertia	The torque stiffness	The axial spring rigidity	Radial spring rigidity	Weight	A	B	C	D	E	F	G
		Eccentricity[mm]	Deflection	Axial displacement												
型号	额定扭矩 [N·m]	偏心 [mm]	偏角 [°]	轴向位移 [m·m]	惯性力矩 [10- 3N·m/rad]	扭矩刚性 [103N·m/rad]	轴向弹簧刚性 [N/mm]	径向弹簧刚性 [N/mm]	质量 [kg]							
LC-F1-15-30	15	0.15	1.5	1	0.07	20	25	475	0.15	30	49	7	25	M5	35	49
LC-F1-15-37	15	0.2	2	2	0.08	15	15	137	0.15	37	49	7	25	M5	35	49
LC-F1-30-36	30	0.2	1.5	1	0.14	39	50	900	0.2	36	55	9	28	M5	37	55
LC-F1-30-44	30	0.25	2	2	0.15	28	30	270	0.2	44	55	9	28	M5	37	55
LC-F1-60-43	60	0.2	1.5	1.5	0.3	76	72	1200	0.3	43	66	10	38	M6	46	66
LC-F1-60-53	60	0.25	2	2	0.32	55	48	420	0.3	53	66	10	38	M6	46	66
LC-F1-80-49	80	0.2	1.5	2	0.8	129	48	920	0.6	49	81	13	50	M6	62	81
LC-F1-80-61	80	0.25	2	3	0.83	85	32	290	0.6	61	81	13	50	M6	62	81
LC-F1-150-50	150	0.2	1.5	2	0.9	175	82	1550	0.6	50	81	13	50	M6	62	81
LC-F1-150-62	150	0.25	2	3	0.95	110	52	435	0.6	62	81	13	50	M6	62	81
LC-F1-200-53	200	0.25	1.5	2	1.3	191	90	2040	0.8	53	90	14	58	M6	70	90
LC-F1-200-65	200	0.3	2.2	3	1.4	140	60	610	0.8	65	90	14	58	M6	70	90
LC-F1-300-56	300	0.25	1.5	2.5	1.95	501	105	3750	1.5	56	110	14	65	M8	80	110
LC-F1-300-70	300	0.3	2.2	3.5	2.1	295	71	1050	1.5	70	110	14	65	M8	80	110
LC-F1-500-64	500	0.3	1.8	2.5	3	510	70	2500	1.4	64	123	16	70	M8	94	122
LC-F1-500-77	500	0.35	2.3	3.5	3.4	500	48	840	1.4	77	123	16	70	M8	94	122
LC-F1-800-81	800	0.35	2.2	3.5	4.3	780	100	2000	1.6	81	133	18	75	M10	90	116
LC-F1-1500-100	1500	0.35	2.2	3.5	10.6	1304	195	3600	3.3	100	157	22	85	M16	110	140
LC-F1-4000-145	4000	0.4	2.5	3.5	46	3400	265	6070	8.9	145	200	30	100	M20	140	182
LC-F1-6000-138	6000	0.4	2.5	3	132	5700	1030	19200	13.9	138	253	30	145	8×M20	190	235
LC-F1-10000-150	10000	0.4	2.5	3	350	10950	985	21800	23.7	150	303	36	190	8×M24	234	295