

Designation	Rated torque [N·m]	最大容许误差 Margin of error		Moment of inertia	The torque stiffness	The largest axial restoring force	Radial spring rigidity	Weight	A	B	C1	C2	D1	D2	E(Locking torque)		F	G	H
		Eccentricity[mm]	Deflection																
型号	额定扭矩 [N·m]	最大容许误差		惯性力矩 [10 ⁻³ N·m/rad]	扭矩刚性 [103N·m/rad]	预应力下联轴器 轴向最大恢复力 [N]	径向弹簧刚性 [N/mm]	质量 [kg]	A	B	C1	C2	D1	D2	E(Locking torque)		F	G	H
		偏心 [mm]	轴向位移 [m·m]																
LC-F6-15-63	15	0.15	0.5	0.1	18	20	475	0.3	63	49	18.5	29	10-22	10-22	M4	3.5	45	9.5	0.2-1.0
LC-F6-15-70	15	0.2	1	0.12	13	12	137	0.32	70	49	18.5	29	10-22	10-22	M4	3.5	45	9.5	0.2-1.0
LC-F6-30-73	30	0.2	0.5	0.2	35	50	900	0.5	73	55	21	34	12-24	12-24	M5	6.5	51	10.5	0.5-1.0
LC-F6-30-81	15	0.25	1	0.25	25	30	270	0.52	81	55	21	34	12-24	12-24	M5	6.5	51	10.5	0.5-1.0
LC-F6-60-83	30	0.2	0.5	0.4	68	70	1200	0.82	83	66	21.5	39	12-32	12-32	M5	8	60	11.5	0.5-1.5
LC-F6-60-93	30	0.25	1	0.45	50	45	420	0.84	93	66	21.5	39	12-32	12-32	M5	8	60	11.5	0.5-1.5
LC-F6-150-104	150	0.2	1	2	158	82	1550	1.6	104	81	30.5	49.8	15-40	15-40	M6	12	74	17.5	0.5-1.5
LC-F6-150-116	150	0.25	2	2.5	100	52	435	1.7	116	81	30.5	49.8	15-40	15-40	M6	12	74	17.5	0.5-1.5
LC-F6-300-123	300	0.25	1.5	5.4	451	157	3750	4.1	123	110	37	59	24-56	24-56	M8	30	102	20	0.5-1.5
LC-F6-300-137	300	0.3	2	6.1	266	106	1050	4.2	137	110	37	59	24-56	24-56	M8	30	102	20	0.5-1.5
LC-F6-500-140	500	0.3	2.5	8.4	460	140	2500	6	140	123	40	68	30-60	30-60	M8	32	114	23	1.0-2.5
LC-F6-500-153	500	0.35	3.5	9.1	450	96	840	6.3	153	123	40	68	30-60	30-60	M8	32	114	23	1.0-2.5
LC-F6-800-150	800	0.35	3	19.5	400	400	2000	9.4	150	133	52	74	40-62	40-62	M10	55	126	27	1.0-2.0
LC-F6-1500-170	1500	0.35	2	44	660	650	3600	16.2	170	157	62	95	50-72	50-72	M12	110	145	32	1.0-2.0