

Bearing Designation	Dimensions							Limited static radial load (pounds)	Limited static axial load (pounds)	Dynamic swing radial torque (pounds)	Weight
	B	D	T	E	O	REF	a°				
	0	0	±.005	0	REF						
型号	-0.0005	0.0005		-0.01	"V"槽直径	球头端面直径	球径	极限静态径向载荷(磅)	极限静态轴向载荷(磅)	动态摆动径向扭矩(磅)	估重(磅)
	球孔	外径	球头宽	衬套宽	"V" aperture diameter	Ball head end diameter	Ball diameter				
WSSB3V	0.19	0.625	0.437	0.327	0.565	0.301	0.531	15	9,000,	1,770	0.031
WSSB4V	0.25	0.625	0.437	0.327	0.565	0.301	0.531	15	9,000	1,770	0.031
WSSB5V	0.3125	0.6875	0.437	0.317	0.627	0.401	0.593	14	9,400	1,640	0.035
WSSB6V	0.375	0.8125	0.5	0.406	0.714	0.471	0.687	8	13,700	2,630	0.06
WSSB7V	0.4375	0.9375	0.562	0.442	0.839	0.542	0.781	10	20.7	3,650	0.08
WSSB8V	0.5	1	0.625	0.505	0.902	0.612	0.875	9	27.5	4,970	0.1
WSSB10V	0.625	1.1875	0.75	0.567	1.089	0.752	1.062	12	39,000	6,130	0.16
WSSB12V	0.75	1.375	0.875	0.63	1.253	0.892	1.25	13	52,300	7,730	0.24
WSSB14V	0.875	1.625	0.875	0.755	1.503	1.061	1.375	6	67,300	10,800	0.35
WSSB16V	1	2.125	1.375	1.005	2.003	1.275	1.875	12	137,000	19,300	0.97